

- Warning** ● Ask a qualified installer or contractor to install this product. Do not try to install the product yourself. Improper installation can result in water or refrigerant leakage, electrical shock, fire or explosion.
- Use only those parts and accessories supplied or specified by Daikin. Ask a qualified installer or contractor to install those parts and accessories. Use of unauthorised parts and accessories or improper installation of parts and accessories can result in water or refrigerant leakage, electrical shock, fire or explosion.
 - Read the user's manual carefully before using this product. The user's manual provides important safety instructions and warnings. Be sure to follow these instructions and warnings.
- If you have any enquiries, please contact your local importer, distributor and/or retailer.

Cautions on product corrosion

1. Air conditioners should not be installed in areas where corrosive gases, such as acid gas or alkaline gas, are produced.
2. If the outdoor unit is to be installed close to the sea shore, direct exposure to the sea breeze should be avoided. If you need to install the outdoor unit close to the sea shore, contact your local distributor.

Dealer

PT. DAIKIN AIRCONDITIONING INDONESIA

HEAD OFFICE:
 Wisma KEJAI 18th Floor
 Jl. Jendral Sudirman Kav.3, Jakarta Pusat 10220
 Telp : +6221 5724 377
 Fax : +6221 5724 360/366
 Website : www.daikin.co.id



Management System
 ISO 9001:2015
 www.tuv.com
 ID 3105084312

- **SERVICE CENTER** : Jakarta Selatan, Telp. : 021-2782 5545 | Samarinda, Telp. : 0541-252 2889
- **WORKSHOP** : Cirebon, Telp. : 0231-8817 512 | Banjarmasin, Tlp. : 0511-6776 838 | Aceh, Tlp. : 0651-7318 036
- Lombok, Tlp. : 0370-7843 231 | Jambi, Tlp. : 0741-3066 790 | Padang, Tlp. : 0751-896 2684
- **TRAINING CENTER** : Sunter, Telp. : 021-650 5030 ● **BRANCH** : Bekasi, Telp. : 021-2945 0585
- Tangerang, Telp. : 021-5314 1195 | Bandung, Telp. : 022-522 5150 | Semarang, Telp. : 024-7660 3221
- Yogyakarta, Telp. : 0274-551 321 | Surabaya, Telp. : 031-503 1138 | Denpasar, Telp. : 0361-900 5514
- Makassar, Telp. : 0411-805 2691 | Palembang, Telp. : 0711-573 2282 | Pekanbaru, Telp. : 0761-561 139
- Medan, Telp. : 061-4200 8866 | Manado, Telp. : 0431-719 1199 | Batam, Tlp. : 0778-4171 445

Daikin Contact Center : 0800 1 081 081 (Toll Free)

DAIKIN CONTACT CENTER
 0800 1 081 081
 BEBAS PULSA
 365 hari/tahun
 Jam Beroperasi :
 Senin - Jumat : 07.00 - 19.00 WIB
 Sabtu - Minggu & Libur Nasional : 08.00 - 17.00 WIB



Cooling Only 50 Hz

R-410A

Exceeding Boundaries with Innovative Energy Savings



New

VRV X

First launched in Japan in 1982, the Daikin **VRV** system has been embraced by world markets for over 35 years. Now, Daikin proudly introduces the new **VRV X** series. By combining the technologies of **VRV**, VRT and VAV, we have attained both energy savings and comfortable air conditioning.

VRV+VRT+VAV

Energy savings

Uniting **VRV**, VRT and VAV technologies


Automatic refrigerant charge function

- Optimised operation efficiency
- Higher installation quality
- Easier installation

High reliability

- New inverter PC board
- Double backup operation
- Refrigerant cooling for PC board

* **VRV** is a trademark of Daikin Industries, Ltd.



RXUQ-A

* To be released in the latter half of 2018. Please contact Daikin sales office for more information.

Cooling Only
6 HP - 60 HP
(16.0 kW) (168 kW)

Advanced technologies for greater energy savings

VRV+VRT+VAI

By uniting advanced **software** and **hardware** technologies for greater energy savings during actual operation and combining the technologies of VRV, VRT and VAV, we have attained both energy savings and comfortable air conditioning.

VRT Smart Control (Fully Automatic Energy-saving Refrigerant Control)

Software technology

Optimally supply only for the needed capacity of indoor units


Daikin developed VRT smart control by combining air volume control (VAV: Variable Air Volume) for indoor units with conventional VRT control, which optimises compressor speed by calculating the required load for the entire system and optimal target refrigerant temperature based on data sent from each indoor unit. Coordination with the air volume control reduces compressor load and minimises operation loss based on detailed control. VRT smart control ensures energy savings and comfortable air conditioning to meet actual operating conditions.



VRT Smart Control Function movie


Overview of the control (system control flow)

Different automatic energy-saving refrigerant control applies depending on the indoor units connected.



The smooth control (which keeps the compressor running) saves energy and ensures comfort during low-load operation.

Changes in the air-conditioned room temperature during low-load operation*



Note:
 • For the classification of indoor units (VRT smart control and VRT control), refer to page 25-26.
 • If a system has indoor units subject to both VRT smart and VRT control, the system is operated under VRT control.
 • If a system has both outdoor-air processing air conditioners and outdoor-air processing type indoor units, VRT smart control and VRT control are disabled.

Optimum utilisation of VRT Smart Control and VRT Control

Effectiveness can be demonstrated for VRT Smart Control and VRT Control when all the indoor units operate under low load conditions in a similar manner.

Low load conditions are the time when room temperature approaches set temperature. For this reason, please note the following to maximise energy efficiency.

When selecting indoor units

Indoor units are installed in a system so that they operate largely under the same conditions. Energy efficiency decreases for the installation patterns shown below.

Example:

- 1) A load imbalance occurs because an indoor unit in the same system is installed near the perimeter of the room or in the vicinity of a room entrance.
- 2) Different operating hours for indoor units.

Time of Use

1. Energy efficiency decreases when the set temperature of a specified indoor unit is excessively lowered during cooling operation.
2. The airflow rate setting is set to "Auto" during VRT Smart Control.


Greater energy savings during low-load operation

The key to innovative energy savings is to increase efficiency during low-load operation.

Using data gathered from actual operation, Daikin discovered that air conditioning systems operate at a load factor of 50% or less for 80% of their annual operation period.


This inspired us to develop new technologies to enhance energy efficiency during low-load operation. Utilising these technologies, Daikin's new VRV X series raises the standard of energy efficiency.

• Correlation between the load factor for the rated capacity and operation time (in office buildings in Singapore)
 * According to a survey by Daikin (based on Air Conditioning Network Service System data)



Higher Coefficient of Performance (COP)

COP for 10 HP



Annual power consumption 20%* lower

* Simulation conditions :
 • Location : Bangkok, Thailand
 • System : Outdoor unit (10 HP) x 1
 Indoor unit (2 HP, Round Flow with Sensing type) x 5
 • Operation time : 8:00-20:00 5 days/week
 • Outdoor units :
 New model : RXUQ10A (VRV X series)
 Conventional model : RXQ10T (VRV IV)




*Cooling operation conditions: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB.

More accurate test operation and stable system

Efficient automatic test operation

Daikin **VRV X** series incorporates a simplified and efficient test operation function, not only greatly accelerating the installation process, but effectively improving the field setting quality as well.


- Automatically checks the wirings between outdoor units and indoor units to confirm whether there is a defective wiring.
- Confirms piping length to optimise operation.
- Automatically checks whether the stop valve in each outdoor unit is in normal status to ensure the smooth operation of air conditioning system.



Simplified commissioning and after-sales service

Function of information display by luminous digital tube


VRV X series utilises 7-segment luminous digital tubes to display system operation information, enabling the operational state to be visually displayed whilst facilitating simplified commissioning and after-sales service.



Advanced control main PC board

SMT* packaging technology


- SMT packaging technology adopted by the whole computer control panel improves the anti-clutter performance.
- Protects your computer boards from the adverse effect of sandy and humid weather.



I-demand function


Limit to power consumption can be set precisely to one of 11 levels. Peak power cut-off can be accomplished according to each user situation.

*Set on the circuit board of the outdoor unit.



Wide operation temperature range up to 49°C


The versatile operation range of the **VRV X** series works to reduce limitations on installation locations. The operation temperature range for cooling can be performed with outdoor temperatures as high as 49°C. This enables reliable operation even under high temperature conditions.



Note: When outdoor temperature falls below 10°C, the thermostat shuts OFF, the outdoor unit stops, and operation switches from cooling to fan operation.

Automatic sequencing operation

During start-up, Daikin **VRV X** series outdoor unit sequencing operation will be automatically enabled to ensure balance operation of each outdoor unit to improve longevity of equipment and operation stability.



Double backup operation functions

Daikin **VRV X** series outdoor unit boasts double backup operation functions, which can secure the use of air conditioners in this area to the greatest extent by emergently enabling double backup operation functions even if failure occurs in a set of air conditioning equipment. In the event of a failure, emergency operation can be conveniently enabled to allow the remaining system to operate in a limited fashion.

Unit backup operation function

If one of the unit in a multiple outdoor system malfunctions, the other outdoor units provide emergency operation until repairs can be made.


* For systems composed of two or more outdoor units.



Compressor backup operation function


The outdoor unit is equipped with two compressors. Even if one compressor malfunctions, the other compressor provides emergency operation, reducing the risk of air conditioning shutdown due to compressor failure. (The capacity is saved during backup operation.)

* For a single outdoor unit system RXUQ14-20AY14 models. On-site settings are required using the printed circuit board of the outdoor unit.



Ease of Maintenance

VRV X series provides maintenance feature* which allows the shutdown of indoor unit without shutting down the whole **VRV** system. This feature comes in handy during maintenance period as the remaining indoor units continue to operate.



* Field setting is required.

This feature does not apply to residential indoor unit connection and is not applicable for all situations. For more information, please contact Daikin sales office.







VRV X Series Outdoor Units



The outdoor unit capacity is up to 60 HP (168 kW) in increment of 2 HP.

- VRV X series outdoor unit offers a high capacity of up to 60 HP, responding to the needs of large-sized building.
- The single outdoor unit has only 2 different shapes and dimensions, not only simplifying the design process, but also bringing the system flexibility to a new level.
- With the outdoor unit capacity increased in increment of 2 HP, customers' needs can be precisely met.

Lineup

CAPACITY (HP)		6	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48	50	52	54	56	58	60	
VRV X SERIES	Single outdoor units	●	●	●	●	●	●	●	●																					
	Double outdoor units				●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●										
	Triple outdoor units							●	●												●	●	●	●	●	●	●	●	●	●

																																									
MODEL		RXUQ6AY14	RXUQ8AY14	RXUQ10AY14	RXUQ12AY14	RXUQ14AY14	RXUQ16AY14	RXUQ18AY14	RXUQ20AY14	RXUQ12AMY14	RXUQ14AMY14	RXUQ16AMY14	RXUQ18AMY14	RXUQ20AMY14	RXUQ18AM1Y14	RXUQ20AM1Y14	RXUQ22AMY14	RXUQ24AMY14	RXUQ26AMY14																						
Combination units		—	—	—	—	—	—	—	—	RXUQ6AY14	RXUQ6AY14	RXUQ8AY14	RXUQ8AY14	RXUQ8AY14	RXUQ6AY14	RXUQ6AY14	RXUQ10AY14	RXUQ12AY14	RXUQ12AY14	RXUQ6AY14	RXUQ8AY14	RXUQ8AY14	RXUQ10AY14	RXUQ12AY14	RXUQ6AY14	RXUQ6AY14	RXUQ12AY14	RXUQ12AY14	RXUQ14AY14												
Power supply		3-phase 4-wire system, 380-415 V, 50 Hz								3-phase 4-wire system, 380-415 V, 50 Hz																															
Cooling capacity	Btu/h	54,600	76,400	95,500	114,000	136,000	154,000	171,000	191,000	109,000	131,000	153,000	172,000	191,000	164,000	186,000	210,000	229,000	251,000																						
	kW	16.0	22.4	28.0	33.5	40.0	45.0	50.0	56.0	32.0	38.4	44.8	50.4	55.9	48.0	54.4	61.5	67.0	73.5																						
Power consumption	kW	3.23	4.82	6.29	7.81	9.46	11.4	12.8	14.8	6.46	8.05	9.64	11.1	12.6	9.69	11.3	14.1	15.6	17.3																						
Capacity control	%	23-100	19-100	13-100	12-100	11-100	9-100		7-100	11-100	10-100	9-100	8-100	7-100	8-100	7-100	6-100																								
Dimensions (HxWxD)	mm	1,657x930x765			1,657x1,240x765						(1,657x930x765)+(1,657x930x765)		(1,657x930x765)+(1,657x1,240x765)		(1,657x930x765)+(1,657x930x765)+(1,657x930x765)				(1,657x1,240x765)+(1,657x1,240x765)																						
Machine weight	kg	185		215		275		291		185+185		185+215		185+185+185		215+215		215+275																							
Sound level	dB(A)	54	56		58	59		62	65	57	58	59		60	59	60		61	62																						

																																								
MODEL		RXUQ28AMY14	RXUQ30AMY14	RXUQ32AMY14	RXUQ34AMY14	RXUQ36AMY14	RXUQ38AMY14	RXUQ40AMY14	RXUQ42AMY14	RXUQ44AMY14	RXUQ46AMY14	RXUQ48AMY14	RXUQ50AMY14	RXUQ52AMY14	RXUQ54AMY14	RXUQ56AMY14	RXUQ58AMY14	RXUQ60AMY14																						
Combination units		RXUQ12AY14	RXUQ12AY14	RXUQ12AY14	RXUQ14AY14	RXUQ16AY14	RXUQ18AY14	RXUQ20AY14	RXUQ12AY14	RXUQ12AY14	RXUQ12AY14	RXUQ12AY14	RXUQ12AY14	RXUQ12AY14	RXUQ14AY14	RXUQ16AY14	RXUQ18AY14	RXUQ20AY14	RXUQ16AY14	RXUQ18AY14	RXUQ20AY14	RXUQ20AY14	RXUQ20AY14	RXUQ20AY14	RXUQ20AY14	RXUQ20AY14	RXUQ20AY14	RXUQ20AY14	RXUQ20AY14	RXUQ20AY14	RXUQ20AY14	RXUQ20AY14	RXUQ20AY14	RXUQ20AY14	RXUQ20AY14	RXUQ20AY14	RXUQ20AY14			
Power supply		3-phase 4-wire system, 380-415 V, 50 Hz								3-phase 4-wire system, 380-415 V, 50 Hz																														
Cooling capacity	Btu/h	268,000	285,000	305,000	328,000	345,000	362,000	382,000	399,000	420,000	444,000	461,000	478,000	498,000	519,000	536,000	553,000	573,000																						
	kW	78.5	83.5	89.5	96.0	101	106	112	117	123	130	135	140	146	152	157	162	168																						
Power consumption	kW	19.2	20.6	22.6	24.3	26.2	27.6	29.6	28.4	30.4	32.1	34.0	35.4	37.4	39.1	41.0	42.4	44.4																						
Capacity control	%	5-100			4-100					4-100	3-100								2-100																					
Dimensions (HxWxD)	mm	(1,657x1,240x765)+(1,657x1,240x765)								(1,657x1,240x765)+(1,657x1,240x765)+(1,657x1,240x765)																														
Machine weight	kg	215+275		215+291		275+291		291+291		215+215+291		215+275+291		215+291+291		275+291+291		291+291+291																						
Sound level	dB(A)	62	63	66		67	68	65	66	67		68	68	69	69	70																								

Note: Specifications are based on the following conditions:
 •Cooling: Indoor temp.: 27°DB, 19°WB, Outdoor temp.: 35°DB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 •Sound level: Anechoic chamber conversion value, measured at a point 1 m in front of the unit at a height of 1.5 m.
 During actual operation, these values are normally somewhat higher as a result of ambient conditions and oil recovery mode.
 When there is concern for noise to the surrounding area such as residences, we recommend investigating the installation location and taking soundproofing measures.


Indoor Unit Lineup

Daikin offers a wide range of indoor units responding to variety of needs of our customers that require air-conditioning solutions.

VRV indoor units

Round Flow Cassette with Sensing and Streamer Type

Comfort, energy savings by sensing functions and enhanced maximum efficiency in cleaning



Round Flow Cassette with Streamer Type

360° airflow for improved comfort and enhanced maximum efficiency in cleaning



Round Flow Cassette with Sensing Type

Comfort and energy savings by sensing functions




Round Flow Cassette Type

360° airflow for improved comfort



Compact Multi Flow Cassette Type

Quiet, compact, and designed for user comfort



Double Flow Cassette Type

Thin, lightweight, and easy to install in narrow ceiling spaces



Single Flow Cassette Type

Compact & elegant design for flexible installation



Single Flow Cassette Type

Slim design for flexible installation



Ceiling Mounted Cassette Duct Type

Unprecedented flexibility with Revolutionary air blow concept



Bedroom Duct Type

Suitable for close living spaces such as hotels and condominiums



Slim Duct (Standard) Type

Slim design, quietness and ideal for drop-ceilings




Slim Duct (Compact) Type

Slim and compact design for easy and flexible installation



Middle Static Pressure Duct Type

Middle static pressure and slim design allow flexible installations.



Middle-High Static Pressure Duct Type

Middle and high static pressure allows for flexible duct design.



High Static Pressure Duct Type

High static pressure allows for flexible duct design.



Outdoor-Air Processing Unit

Combine fresh air treatment and air conditioning, supplied from a single system.



Outdoor-Air Processing Unit

Improve IAQ with fresh air ventilation and precise room temperature control



Ceiling Suspended Type

Slim body with quiet and wide airflow.



Wall Mounted Type

Stylish flat panel design harmonised with your interior décor.



Floor Standing Type / Conceal Floor Standing Type

Suitable for perimeter zone air conditioning



Floor Standing Duct Type

Large airflow type for large spaces.



Clean Room Air Conditioner

Suitable for hospitals and other clean spaces



Air Handling Unit

Integrate your air handling unit in a total solution for large size spaces such as factories and large stores.



Air treatment equipment

Heat Reclaim Ventilator with DX-Coil

Air quality improvement by introducing fresh outdoor air in the room



Heat Reclaim Ventilator

Daikin VAM series ensures fresh air intake and energy savings



Ceiling Mounted Cassette (Round Flow with Sensing) Type

FXFSQ-A

Round flow with sensing



Ceiling Mounted Cassette (Round Flow) Type

FXFQ-A

ROUND FLOW



Wide variety of decoration panels (Option)

• Designer choice has been given a boost with the increase in number of new types of decoration panels.



Decoration Panel Lineup (Option)



FXFSQ series only
Standard panel with sensing^{**1}
BYCQ125EEF (Fresh White)



Standard panel^{**2}
BYCQ125EAF (Fresh White)



Designer panel^{**2}
BYCQ125EAPF (Fresh White)



Auto grille panel^{**2}
BYCQ125EASF (Fresh White)



FXFSQ series only
Standard panel with sensing^{**1}
BYCQ125EEK (Black)



Standard panel^{**2}
BYCQ125EAK (Black)

*1. Sensing function is applicable when sensing panel is installed.
*2. These panels do not contain the sensing function.

Specifications

Ceiling Mounted Cassette (Round Flow with Sensing) Type

MODEL	FXFSQ25AV4	FXFSQ32AV4	FXFSQ40AV4	FXFSQ50AV4	FXFSQ63AV4	FXFSQ80AV4	FXFSQ100AV4	FXFSQ125AV4	FXFSQ140AV4	
Power supply	1-phase, 220-240 V/220-230 V, 50/60 Hz									
Cooling capacity	Btu/h	9,600	12,300	15,400	19,100	24,200	30,700	38,200	47,800	54,600
Power consumption	kW	0.028		0.035	0.038	0.061	0.092	0.144	0.170	0.194
Casing	Galvanised steel plate									
Sound level (H/HM/M/ML/L)	dB(A)	30/29.5/28.5/28/27		35/29.5/29/28/27	38/35/34.5/29.5/27	38/36/35.5/31.5/28	39/37/36/35.5/31	44/41/38/35/33	45/42.5/39.5/37/35	46/43.5/40.5/38/35
Dimensions (HxWxD)	mm	256x840x840						298x840x840		
Machine weight	kg	19			24	22	25		26	

Ceiling Mounted Cassette (Round Flow) Type

MODEL	FXFQ25AV4	FXFQ32AV4	FXFQ40AV4	FXFQ50AV4	FXFQ63AV4	FXFQ80AV4	FXFQ100AV4	FXFQ125AV4	FXFQ140AV4	
Power supply	1-phase, 220-240 V/220-230 V, 50/60 Hz									
Cooling capacity	Btu/h	9,600	12,300	15,400	19,100	24,200	30,700	38,200	47,800	54,600
Power consumption	kW	0.029		0.036	0.040	0.063	0.096	0.158	0.178	0.203
Casing	Galvanised steel plate									
Sound level (H/HM/M/ML/L)	dB(A)	30/29.5/28.5/28/27		35/29.5/29/28/27	35/33.5/29.5/28.5/27	36/35.5/31.5/31/28	37/36.5/36/35.5/29.5	43/40.5/37.5/35/33	44/41.5/39/36.5/33	46/43.5/40.5/38/35
Dimensions (HxWxD)	mm	256x840x840						298x840x840		
Machine weight	kg	19				22	25		26	

Note: Specifications are based on the following conditions;

- Cooling: Indoor temp.: 27°CDB, 19°CWB, Outdoor temp.: 35°CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.
- Capacity of indoor unit is only for reference. Actual capacity of indoor unit is based on the total capacity index. (See Engineering Data Book for details.)
- Sound level: Anechoic chamber conversion value, measured at a point 1.5 m downward from the unit centre.

During actual operation, these values are normally somewhat higher as a result of ambient conditions.

Compact Multi Flow Cassette Type


New FXZQ-B

Quiet, compact, and designed for user comfort



Compact & elegant design

- Fully-flat integration in standard architectural ceiling tiles, leaving only 8 mm
- Remarkable blend of iconic design and engineering excellence with an elegant finish in white
- The newly designed panel integrates fully within one ceiling tile enabling lights, speakers and sprinklers to be installed in the adjoining ceiling tiles.



Efficiency & comfort

Dual sensors (Option)

- Two optional intelligent sensors improve energy efficiency and comfort.
- An optional presence and floor sensor kit can be fitted to the cassette for draught prevention, energy-saving operation and to provide optimal control of airflow.



Individual airflow direction control*

- Airflow direction can be individually adjusted for each air discharge outlet to deliver optimal air distribution.

*Applicable when wired remote controller BRC1E63 or BRC1H63W(K) is used.

Auto swing (up/down)

- Possibility to select automatic vertical moving of the air discharge flaps for efficient air and temperature distribution throughout the room.



Cleanliness

New Streamer filter clean unit (Option) See page 3-4

Daikin Streamer technology enhances maximum efficiency in cleaning, which uses powerful decomposition properties to decompose substances captured by the filter for better air quality.

Remarks:

- 1) Only the stylish remote controller BRC1H63W(K) can be connected for ON/OFF operation of the streamer.
- 2) The Streamer function operates only when the fan and air conditioning operation are stopped. The maximum operation of Streamer is 180 minutes per day.



BAPW55A61

Ceiling soiling prevention

- Prevents air from blowing against the ceiling to prevent ceiling stains.

Slim Ceiling Mounted Duct Type (Standard Series) FXDQ-PD / ND

Slim design, quietness and static pressure switching



Specifications

MODEL	with drain pump	FXDQ20PDVE4	FXDQ25PDVE4	FXDQ32PDVE4	FXDQ40NDVE4	FXDQ50NDVE4	FXDQ63NDVE4
	without drain pump	FXDQ20PDVET4	FXDQ25PDVET4	FXDQ32PDVET4	FXDQ40NDVET4	FXDQ50NDVET4	FXDQ63NDVET4
Power supply	1-phase, 220-240 V/220 V, 50/60 Hz						
Cooling capacity	Btu/h	7,500	9,600	12,300	15,400	19,100	24,200
Power consumption	kW	0.086	0.086	0.089	0.160	0.165	0.181
Power consumption (FXDQ-PDVE) *1	kW	0.067	0.067	0.070	0.147	0.152	0.168
External static pressure	Pa	30-10*2			44-15*2		
Sound level (HH/H/L)*1*3	dB(A)	28/26/23		28/26/24	30/28/26	33/30/27	33/31/29
Dimensions (HxWxD)	mm	200x700x620	200x700x620	200x700x620	200x900x620	200x900x620	200x1,100x620
Machine weight	kg	23	23	23	27	28	31

Note: Specifications are based on the following conditions:
 •Cooling: Indoor temp.: 27°CDB, 19°CWB, Outdoor temp.: 35°CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 •Capacity of indoor unit is only for reference. Actual capacity of indoor unit is based on the total capacity index. (See Engineering Data Book for details.)
 •Sound level: Anechoic chamber conversion value, measured at a point 1.5 m downward from the unit centre.
 During actual operation, these values are normally somewhat higher as a result of ambient conditions.
 *1 : Values are based on the following conditions: FXDQ-PD: external static pressure of 10 Pa; FXDQ-ND: external static pressure of 15 Pa.
 *2 : External static pressure is changeable to set by the remote controller. This pressure means "High static pressure - Standard". (Factory setting is 10 Pa for FXDQ-PD models and 15 Pa for FXDQ-ND models.)
 *3 : The values of operation sound level represent those for rear-suction operation. Sound level values for bottom-suction operation can be obtained by adding 5 dB(A).

Slim Ceiling Mounted Duct Type (Compact Series) FXDQ-SP

Slim and compact design for easy and flexible installation



Specifications

MODEL	FXDQ20SPV14	FXDQ25SPV14	FXDQ32SPV14	FXDQ40SPV14	FXDQ50SPV14	FXDQ63SPV14
	Power supply	1-phase, 220-240 V, 50 Hz				
Cooling capacity	Btu/h	7,500	9,600	12,300	15,400	19,100
Power consumption *1	kW	0.072	0.075	0.078	0.180	0.196
Airflow rate (HH/H/L)	m³/min	8.7/7.6/6.5	9.0/8.0/7.0	10.0/9.0/8.0	15.0/13.0/10.5	
	cfm	307/268/229	318/282/247	353/318/282	530/459/371	
External static pressure	Pa	30-10*2		50-20*2		40-20*2
Sound level (HH/H/L)*1*3	dB(A)	33/31/29		34/32/30	35/33/31	37/35/33
Dimensions (HxWxD)	mm	200x700x450			200x900x450	200x1,100x450
Machine weight	kg	17			20	23

Note: Specifications are based on the following conditions:
 •Cooling: Indoor temp.: 27°CDB, 19°CWB, Outdoor temp.: 35°CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 •Capacity of indoor unit is only for reference. Actual capacity of indoor unit is based on the total capacity index. (See Engineering Data Book for details.)
 •Sound level: Anechoic chamber conversion value, measured at a point 1.5 m downward from the unit centre.
 During actual operation, these values are normally somewhat higher as a result of ambient conditions.
 *1 : Values are based on the following conditions: FXDQ20-32SP: external static pressure of 10 Pa; FXDQ40-63SP: external static pressure of 20 Pa.
 *2 : External static pressure is changeable to set by the remote controller. This pressure means "High static pressure - Standard". (Factory setting is 10 Pa for FXDQ20-32SP models and 20 Pa for FXDQ40-63SP models.)
 *3 : The values of operation sound level represent those for rear-suction operation. Sound level values for bottom-suction operation can be obtained by adding 5 dB(A).

Ceiling Mounted Duct Type FXMQ-PA / MA / P

Middle and high static pressure allows for flexible duct design



Specifications

MODEL	FXMQ20PAV4	FXMQ25PAV4	FXMQ32PAV4	FXMQ40PAV4	FXMQ50PAV4
Power supply	1-phase, 220-240 V/220 V, 50/60 Hz				
Cooling capacity	Btu/h	7,500	9,600	12,300	15,400
Power consumption	kW	0.056*1	0.056*1	0.060*1	0.151*1
Airflow rate (HH/H/L)	m³/min	9/7.5/6.5	9/7.5/6.5	9.5/8/7	16/13/11
	cfm	318/265/230	318/265/230	335/282/247	565/459/388
External static pressure	Pa	30-100 (50)*2		30-100 (50)*2	30-160 (100)*2
Sound level (HH/H/L)	dB(A)	33/31/29		34/32/30	39/37/35
Dimensions (HxWxD)	mm	300x550x700		300x550x700	300x700x700
Machine weight	kg	25		25	35

MODEL	FXMQ63PAV4	FXMQ80PAV4	FXMQ100PAV4	FXMQ125PAV4	FXMQ140PAV4
Power supply	1-phase, 220-240 V/220 V, 50/60 Hz				
Cooling capacity	Btu/h	24,200	30,700	38,200	47,800
Power consumption	kW	0.138*1	0.185*1	0.215*1	0.284*1
Airflow rate (HH/H/L)	m³/min	19.5/17.5/16	25/22.5/20	32/27/23	39/33/28
	cfm	688/618/565	883/794/706	1,130/953/812	1,377/1,165/988
External static pressure	Pa	50-200 (100)*2		50-200 (100)*2	50-200 (100)*2
Sound level (HH/H/L)	dB(A)	42/40/38	43/41/39	43/41/39	44/42/40
Dimensions (HxWxD)	mm	300x1,000x700		300x1,000x700	300x1,400x700
Machine weight	kg	35		45	46

Note: Specifications are based on the following conditions:
 •Cooling: Indoor temp.: 27°CDB, 19°CWB, Outdoor temp.: 35°CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 •Capacity of indoor unit is only for reference. Actual capacity of indoor unit is based on the total capacity index. (See Engineering Data Book for details.)
 •Sound level: Anechoic chamber conversion value, measured at a point 1.5 m downward from the unit centre.
 During actual operation, these values are normally somewhat higher as a result of ambient conditions.
 *1 : Power consumption values are based on conditions of rated external static pressure.
 *2 : External static pressure can be modified using a remote controller that offers seven (FXMQ20-32PA), thirteen (FXMQ40PA), fourteen (FXMQ50-125PA) or ten (FXMQ140PA) levels of control. These values indicate the lowest and highest possible static pressures. The standard static pressure is 50 Pa for FXMQ20-32PA and 100 Pa for FXMQ40-140PA.

High static pressure allows for flexible duct design



FXMQ200-250PVM4

Specifications

MODEL	FXMQ200MAV4	FXMQ250MAV4	FXMQ200PVM	FXMQ250PVM
Power supply	1-phase, 220-240 V/220 V, 50/60 Hz			
Cooling capacity	Btu/h	76,400	95,500	76,400
Power consumption	kW	1.294*1	1.465*1	0.55*1
Airflow rate (H/L)	m³/min	58/50	72/62	61/50
	cfm	2,047/1,765	2,542/2,189	2,153/1,765
External static pressure	Pa	132-221*2		191-270*2
* Sound level (H/L)	220 V	48/45		38/35
	240 V	49/46		40/37
Dimensions (HxWxD)	mm	470x1,380x1,100		470x1,490x1,100
Machine weight	kg	137		105

Note: Specifications are based on the following conditions:
 •Cooling: Indoor temp.: 27°CDB, 19°CWB, Outdoor temp.: 35°CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 •Capacity of indoor unit is only for reference. Actual capacity of indoor unit is based on the total capacity index. (See Engineering Data Book for details.)
 •Sound level: (FXMQ-MA) Anechoic chamber conversion value, measured at a point 1.5 m downward from the unit centre.
 During actual operation, these values are normally somewhat higher as a result of ambient conditions.
 1: Power consumption values are based on conditions of standard external static pressure.
 2: External static pressure is changeable to change over the connectors inside electrical box, this pressure means "Standard-High static pressure".

Middle Static Pressure Ceiling Mounted Duct Type FXSQ-PA

Middle external static pressure and slim design allow flexible installations



Specifications

MODEL		FXSQ20PAV4	FXSQ25PAV4	FXSQ32PAV4	FXSQ40PAV4	FXSQ50PAV4
Power supply		1-phase, 220-240 V/220 V, 50/60 Hz				
Cooling capacity	Btu/h	7,500	9,600	12,300	15,400	19,100
Power consumption	kW	0.058 *1	0.058 *1	0.066 *1	0.101 *1	0.075 *1
Airflow rate (H/M/L)	m ³ /min	9/7.5/6.5	9/7.5/6.5	9.5/8/7	15/12.5/10.5	17/14.5/11.5
	cfm	318/265/230	318/265/230	335/282/247	530/441/371	600/512/406
External static pressure	Pa	30-150 (50) *2				
Sound level (H/M/L)	dB(A)	33/30/28		34/32/30	36/33/30	34/32/29
Dimensions (HxWxD)	mm	245x550x800			245x700x800	245x1,000x800
Machine weight	kg	25			27	35

MODEL		FXSQ63PAV4	FXSQ80PAV4	FXSQ100PAV4	FXSQ125PAV4	FXSQ140PAV4
Power supply		1-phase, 220-240 V/220 V, 50/60 Hz				
Cooling capacity	Btu/h	24,200	30,700	38,200	47,800	54,600
Power consumption	kW	0.106 *1	0.126 *1	0.151 *1	0.206 *1	0.222 *1
Airflow rate (H/M/L)	m ³ /min	21/17.5/14.5	23/19.5/16	32/27/22.5	37/31.5/26	39/33.5/28
	cfm	741/618/512	812/688/565	1,130/953/794	1,306/1,112/918	1,377/1,183/988
External static pressure	Pa	50-150 (50) *2				
Sound level (H/M/L)	dB(A)	36/32/29	37.5/34/30	39/35/32	42/38.5/35	43/40/36
Dimensions (HxWxD)	mm	245x1,000x800		245x1,400x800		245x1,550x800
Machine weight	kg	35	37	46	47	52

Note: Specifications are based on the following conditions;
 •Cooling: Indoor temp.: 27°CDB, 19°CWB, Outdoor temp.: 35°CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 •Capacity of indoor unit is only for reference. Actual capacity of indoor unit is based on the total capacity index. (See Engineering Data Book for details.)
 •Sound level: Anechoic chamber conversion value, measured at a point 1.5 m downward from the unit centre.
 During actual operation, these values are normally somewhat higher as a result of ambient conditions.
 *1: Power consumption values are based on conditions of rated external static pressure.
 *2: External static pressure can be modified using a remote controller that offers thirteen (FXSQ20-40PA), eleven (FXSQ50-125PA) or ten (FXSQ140PA) levels of control. These values indicate the lowest and highest possible static pressures. The rated static pressure is 50 Pa.

Ceiling Suspended Type FXHQ-MA / A

Slim body with quiet and wide airflow



Specifications

MODEL		FXHQ32MAV7	FXHQ63MAV7	FXHQ100MAV7	FXHQ125AVM4	FXHQ140AVM4
Power supply		1-phase, 220-240 V/220 V, 50/60 Hz				
Cooling capacity	Btu/h	12,300	24,200	38,200	48,000	52,900
Power consumption	kW	0.111	0.115	0.135	0.168	0.181
Airflow rate (H/L)	m ³ /min	12/10	17.5/14	25/19.5	34/20	36/20
	cfm	424/353	618/494	883/688	1,200/706	1,271/706
Sound level (H/L)	dB(A)	36/31	39/34	45/37	46/37	48/37
Dimensions (HxWxD)	mm	195x960x680	195x1,160x680	195x1,400x680	235x1,590x690	235x1,590x690
Machine weight	kg	24.0	28.0	33.0	39.0	

Note: Specifications are based on the following conditions;
 •Cooling: Indoor temp.: 27°CDB, 19°CWB, Outdoor temp.: 35°CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 •Capacity of indoor unit is only for reference. Actual capacity of indoor unit is based on the total capacity index. (See Engineering Data Book for details.)
 •Sound level: Anechoic chamber conversion value, measured at a point 1 m in front of the unit and 1 m downward.
 During actual operation, these values are normally somewhat higher as a result of ambient conditions.

Wall Mounted Type FXAQ-AVM

Stylish flat panel design harmonised with your interior décor



Specifications

MODEL		FXAQ20AVM(4)(S)	FXAQ25AVM(4)(S)	FXAQ32AVM(4)(S)	FXAQ40AVM(4)(S)	FXAQ50AVM(4)(S)	FXAQ63AVM(4)(S)
Power supply		VM: 1-phase, 220-240 V/220-230 V, 50/60 Hz VM4, VMS: 1-phase, 220 V, 50 Hz					
Cooling capacity	Btu/h	7,500	9,600	12,300	15,400	19,100	24,200
Power consumption	kW	0.040			0.050	0.060	0.100
Airflow rate (H/L)	m ³ /min	9.1/7.0	9.4/7.0	9.8/7.0	12.2/9.7	15.0/12.0	19.0/14.0
	cfm	321/247	332/247	346/247	431/342	530/424	671/494
Sound level (H/L)	dB(A)	33.0/28.5	35.0/28.5	37.5/28.5	37.0/33.5	41.0/35.5	46.5/38.5
Dimensions (HxWxD)	mm	290x795x266			290x1,050x269		
Machine weight	kg	12.0			15.0		

Note: Specifications are based on the following conditions;
 •Cooling: Indoor temp.: 27°CDB, 19°CWB, Outdoor temp.: 35°CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 •Heating: Indoor temp.: 20°CDB, Outdoor temp.: 7°CDB, 6°CWB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 •Capacity of indoor unit is only for reference. Actual capacity of indoor unit is based on the total capacity index. (See Engineering Data Book for details.)
 •Sound level: Anechoic chamber conversion value, measured at a point 1 m in front of the unit and 1 m downward.
 During actual operation, these values are normally somewhat higher as a result of ambient conditions.

Ceiling Mounted Cassette Duct Type FXFDQ-AV4

Unprecedented Flexibility with Revolutionary Air Blow Concept



Specifications

MODEL		FXFDQ63AV4	FXFDQ80AV4	FXFDQ100AV4	FXFDQ125AV4
Power supply		1-phase, 220 V, 50 Hz			
Cooling capacity	Btu/h	24,200	30,700	38,200	47,800
Power consumption	kW	0.063	0.096	0.158	0.178
Airflow rate (H/M/L)	m ³ /min	21/20/16/15/13.5	22.5/21.5/21/20/15	32/29/26/23/21	33/30.5/28/25.5/21
	cfm	741/706/565/530/477	794/759/741/706/530	1,130/1,024/918/812/741	1,165/1,077/988/900/741
Sound level (H/M/L)	dB(A)	40/38.5/37/35.5/34	43/41.5/40/38.5/37	46.5/45/43.5/42/40.5	46.5/45/43.5/42/40.5
Dimensions (HxWxD)	mm	298x840x840			
Machine weight	kg	26			

Note: Specifications are based on the following conditions;
 •Cooling: Indoor temp.: 27°CDB, 19°CWB, Outdoor temp.: 35°CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 •Capacity of indoor unit is only for reference. Actual capacity of indoor unit is based on the total capacity index. (See Engineering Data Book for details.)
 •Sound level: (FXUQ-A) Anechoic chamber conversion value, measured at a point 1 m in front of the unit and 1 m downward.
 During actual operation, these values are normally somewhat higher as a result of ambient conditions
 1: Power consumption values are based on conditions of standard external static pressure.
 2: External static pressure is changeable to change over the connectors inside electrical box, this pressure means "Standard-High static pressure".

Floor Standing Type

FXLQ-MA

Suitable for perimeter zone air conditioning



Specifications

MODEL		FXLQ20MAVE4	FXLQ25MAVE4	FXLQ32MAVE4	FXLQ40MAVE4	FXLQ50MAVE4	FXLQ63MAVE4
Power supply		1-phase, 220-240 V/220 V, 50/60 Hz					
Cooling capacity	Btu/h	7,500	9,600	12,300	15,400	19,100	24,200
Power consumption	kW	0.049	0.049	0.090	0.090	0.110	0.110
Airflow rate (H/L)	m ³ /min	7/6	7/6	8/6	11/8.5	14/11	16/12
	cfm	247/212	247/212	282/212	388/300	494/388	565/424
Sound level (H/L)	220 V	35/32	35/32	35/32	38/33	39/34	40/35
	240 V	37/34	37/34	37/34	40/35	41/36	42/37
Dimensions (H×W×D)	mm	600×1,000×222	600×1,000×222	600×1,140×222	600×1,140×222	600×1,420×222	600×1,420×222
Machine weight	kg	25.0	25.0	30.0	30.0	36.0	36.0

Note: Specifications are based on the following conditions;

- Cooling: Indoor temp.: 27°CDB, 19°CWB, Outdoor temp.: 35°CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.
- Capacity of indoor unit is only for reference. Actual capacity of indoor unit is based on the total capacity index. (See Engineering Data Book for details.)
- Sound level: Anechoic chamber conversion value, measured at a point 1.5 m in front of the unit at a height of 1.5 m. During actual operation, these values are normally somewhat higher as a result of ambient conditions.

Floor Standing Duct Type

FXVQ-N

Large airflow type for large spaces.
Flexible interior design for each tenant.



Specifications

MODEL		FXVQ125NY14	FXVQ200NY14	FXVQ250NY14	FXVQ400NY14	FXVQ500NY14
Power supply		3-phase 4-wire system, 380-415 V, 50 Hz				
Cooling capacity	Btu/h	47,800	76,400	95,500	154,000	191,000
		0.53	1.33	1.61	3.97	2.62
Dimensions (H×W×D)	mm	1,670×750×510	1,670×950×510	1,670×1,170×510	1,900×1,170×720	1,900×1,470×720
Machine weight	kg	118	144	169	236	281
Sound level *1	dB(A)	52	56	60	65	62
Air filter	Type	Long-life filter (anti-mould resin net)				
Fan	Motor output	kW		3.7		
	Airflow rate	m ³ /min		165		
		cfm		5,825		
	External static pressure *2	Pa		142		

Note: Specifications are based on the following conditions;

- Cooling: Indoor temp.: 27°CDB, 19°CWB, Outdoor temp.: 35°CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.
- Capacity of indoor unit is only for reference. Actual capacity of indoor unit is based on the total capacity index. (See Engineering Data Book for details.)

*1: Sound level : measured when the air discharge outlet duct (2 m) is attached (anechoic chamber conversion value).

It increases by approximately 5 dB(A) when the plenum chamber is installed to deliver direct airflow.

*2: The value is the external static pressure with standard pulley.

Concealed Floor Standing Type

FXNQ-MA

Designed to be concealed
in the perimeter skirting-wall



Specifications

MODEL		FXNQ20MAVE4	FXNQ25MAVE4	FXNQ32MAVE4	FXNQ40MAVE4	FXNQ50MAVE4	FXNQ63MAVE4
Power supply		1-phase, 220-240 V/220 V, 50/60 Hz					
Cooling capacity	Btu/h	7,500	9,600	12,300	15,400	19,100	24,200
Power consumption	kW	0.049	0.049	0.090	0.090	0.110	0.110
Airflow rate (H/L)	m ³ /min	7/6	7/6	8/6	11/8.5	14/11	16/12
	cfm	247/212	247/212	282/212	388/300	494/388	565/424
Sound level (H/L)	220 V	35/32	35/32	35/32	38/33	39/34	40/35
	240 V	37/34	37/34	37/34	40/35	41/36	42/37
Dimensions (H×W×D)	mm	610×930×220	610×930×220	610×1,070×220	610×1,070×220	610×1,350×220	610×1,350×220
Machine weight	kg	19.0	19.0	23.0	23.0	27.0	27.0

Note: Specifications are based on the following conditions;

- Cooling: Indoor temp.: 27°CDB, 19°CWB, Outdoor temp.: 35°CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.
- Capacity of indoor unit is only for reference. Actual capacity of indoor unit is based on the total capacity index. (See Engineering Data Book for details.)
- Sound level: Anechoic chamber conversion value, measured at a point 1.5 m in front of the unit at a height of 1.5 m. During actual operation, these values are normally somewhat higher as a result of ambient conditions.

Clean Room Air Conditioner

FXB(P)Q-P

Suitable for hospitals and
other clean spaces



Specifications

Type		Integrated outlet unit model			Separate outlet unit model
MODEL	Indoor unit	FXBQ40PVE	FXBQ50PVE	FXBQ63PVE	FXBPQ63PVE
	Outlet unit	Integrated with the indoor unit			BAF82A63
Power supply		1-phase, 220-240 V/220 V, 50/60 Hz			
Cooling capacity	Btu/h	15,400	19,100	24,200	24,200
Power consumption	kW	0.31	0.31	0.45	0.45
Intake filter efficiency *1		70% by gravimetric method			
Outlet HEPA filter efficiency *2		99.97% by DOP method *5			
Indoor unit weight	kg	140 *3		185 *3	120 *6
Casing		Galvanised steel plate			
Airflow rate (H/L)	m ³ /min	19.5/17.5		26/22.5	
	cfm	688/618		918/794	
Sound level (H/L) *4	dB(A)	44/42			
Dimensions (H×W×D)	mm	492×1,788×1,000		492×1,788×1,300	492×1,078×1,300
Outlet unit weight	kg	-			65 *3

Note: Specifications are based on the following conditions;

- Cooling: Indoor temp.: 27°CDB, 19°CWB, Outdoor temp.: 35°CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.
- Capacity of indoor unit is only for reference. Actual capacity of indoor unit is based on the total capacity index. (See Engineering Data Book for details.)

*1: An intake air filter is only attached to the ceiling intake type.

*2: HEPA filter sold separately. The dust collection efficiency of HEPA filter is 99.97%. However, air may slightly leak around the filter when installing.

*3: Weight including HEPA filter and panel.

*4: Anechoic chamber conversion value under JIS B 8616 test conditions. Value usually increases slightly in practice due to surrounding conditions.

*5: The clean room air conditioner does not support DOP testing (leak test) based on GMP standards (Standards for Manufacturing Control and Quality Control for Medical Devices) due to slight leakage at time of product installation.

*6: Weight including panel.

*In the case of an installation in an operating theatre etc. where an air conditioner malfunction may have serious consequences, please build in redundancy with two or more outdoor units.

Indoor Unit Lineup

Slim Ceiling Mounted Duct Type

FDKS-EA/C

Slim and smooth design suits your shallow ceiling



Standard accessory
Note: Remote controllers other than the standard accessory wireless remote controller cannot be used.

Specifications

MODEL	FDKS25EAVMB	FDKS35EAVMB	FDKS25CAVMB	FDKS35CAVMB	FDKS50CVMB	FDKS60CVMB
Power supply	1-phase, 220-240 V/220-230 V, 50/60 Hz					
Airflow rates (H)	8.7 (307)		9.5 (335)		10.0 (353)	
Sound levels (H/L/SL)*	35/31/29		37/33/31		38/34/32	
Fan speed	5 steps, quiet and automatic					
Temperature control	Microcomputer control					
Dimensions (HxWxD)	200x700x620		200x900x620		200x1,100x620	
Machine weight	21		25		27	
External static pressure	30		40			

Note: * The operation sound level values represent those for rear-suction operation and an external static pressure of 30 Pa for FDKS-EA and 40 Pa for FDKS-C. Sound level values for bottom-suction operation can be obtained by adding 6 dB (A) for FDKS-EA and 5 dB (A) for FDKS-C.

Residential indoor Units with connection to BP units

Wall Mounted Type

FTKS-D/B/F

Stylish flat panel harmonises with your interior décor



FTKS25D / FTKS35D



Standard accessory*



FTKS60F / FTKS71F



Standard accessory*

* Remote controllers other than the standard accessory wireless remote controller cannot be used.

Specifications

MODEL	FTKS25DVM	FTKS35DVM	FTKS60FVM	FTKS71FVM
Power supply	1-phase, 220-240 V/220-230 V, 50/60 Hz			
Front panel colour	White			
Airflow rates (H)	8.7 (307)		8.9 (314)	
Sound levels (H/L/SL)	37/25/22		39/26/23	
Fan speed	5 steps, quiet and automatic			
Dimensions (HXWxD)	283x800x195		290x1,050x238	
Machine weight	9		12	

Wall Mounted Type

FTKJ-N

Elegant appearance with European style



Standard accessory



Specifications

MODEL	FTKJ25NVMW	FTKJ25NVMS	FTKJ35NVMW	FTKJ35NVMS	FTKJ50NVMW	FTKJ50NVMS
Power supply	1-phase, 220-240 V/220-230 V, 50/60 Hz					
Front panel colour	White		Silver		White	
Airflow rates (H)	8.9 (313)		10.9 (385)			
Sound levels (H/L/SL)	38/25/19		45/26/20		46/35/29	
Fan speed	5 steps, quiet and automatic					
Dimensions (HxWxD)	303x998x212					
Machine weight	12					

BP Units for Connection to Residential Indoor Units

Specifications



BPMKS967A3



BPMKS967A2

MODEL	BPMKS967A3	BPMKS967A2
Power supply	1-phase, 220-240 V/220-230 V, 50/60 Hz	
Number of ports	3 (connectable to 1-3 indoor units)	
Power consumption	10	
Running current	0.05	
Dimensions (HXWxD)	180X294 (+356*)X350	
Machine weight	8	
Number of wiring connections	2 (for power supply (including earth wiring), 2 for interunit wiring (outdoor unit-BP, BP-BP), 4 for interunit wiring (BP-indoor unit))	
Piping connections (Brazing)	Ø9.5X1	
Heat insulation	Both liquid and gas pipes	
Connectable indoor units	2.0 kW class to 7.1 kW class	
Min. rated capacity of connectable indoor units	2.0	
Max. rated capacity of connectable indoor units	20.8	

Note: * Total auxiliary piping length.

PM2.5 filtration unit

Double-layered efficient filtration

1. The front filter effectively removes large particles.
2. The PM2.5 filter layer contains a large amount of static electricity to capture particulate matter efficiently.

Optional :
Active Carbon Filtration Unit




Air Handling Unit

Integrate your air handling unit in a total solution for large size spaces such as factories and large stores.


- Easy design and installation
The system is easy to design and install since no additional water systems such as boilers, tanks and gas connections etc are required.
- Inverter controlled units
- Control of air temperature via standard Daikin wired remote control for standard series



AHUR
Capacity range : 6 – 120 HP




Daikin air handling units can be connected to **VRV** systems. This combination can be built to order as a system. Outdoor air series is also possible. Please contact your local sales office for details.



Air Treatment Equipment

Daikin's air treatment systems creating a higher IAQ

Components of indoor air quality



A recent trend rapidly gaining popularity is for air treatment to be required as well as air conditioning. Daikin has a lineup of 3 products that provide adequate IAQ, according to the client's needs.

Our Solutions for Indoor Air Quality Problems

You may think cool and comfortable air-conditioned room is enough, but...

1 If the windows are closed in an air-conditioned room
Virus and CO₂ will accumulate in the room.

2 But if you open the windows...
PM2.5 and humidity will come in, and it will become hot.

3 Let's close the windows and turn on the air purifier!
Air conditioning regulates heat and humidity, and air purifier can remove PM2.5, but CO₂ remains high. It is hard to concentrate.

4 If you have mechanical ventilation system such as Heat Reclaim Ventilator...
Finally, the CO₂ has been removed, and a comfortable space has been achieved!

Ventilation equipment can be selected according to suit purpose and circumstances

	Outdoor Air Processing Unit		Heat Reclaim Ventilator	
	FXMQ-MF series	FXMQ-BF series	VKM-GC series	VAM-H series
Connections with VRV systems	Refrigerant Piping	Connectable	Connectable	Not connectable
	Wiring	Connectable	Connectable	Connectable
	After-cool & After-heat Control	Available	Available	Not available
Ventilation class		Class 2	Class 1	Class 1
		Air supply only	Air supply & air exhaust	Air supply & air exhaust
Heat Exchange Element	—	—	Energy savings obtained	Energy savings obtained
High Efficiency Filter (Option)	Available	—	Available	Available
PM2.5 Filter (Option)	—	—	Available	Available
MERV8/14 Filter (Option)	—	Available	—	—
Airflow Rate	1,080 - 2,100 m ³ /h	690 - 2,160 m ³ /h	500 - 950 m ³ /h	150 - 2,000 m ³ /h

*1. Optional filter is necessary. Refer to option list for details.
*2. Refers to bringing outdoor air to near indoor temperature and delivering to a room.

Ventilation class

Class 1 Ventilation	Class 2 Ventilation	Class 3 Ventilation
Installing a Heat Reclaim Ventilator enables mechanical ventilation to control both air supply and air exhaust while ensuring continuous room comfort through the supply of temperature-controlled air.	Mechanical ventilation is used for air supply, and natural ventilation is used for air exhaust. This prevents dirty outdoor air from entering and maintains a clean environment even for large spaces.	Natural ventilation is used for air supply, and mechanical ventilation is used for air exhaust. Odours and steam generated indoors are eliminated before spreading to other areas.

Air Treatment Equipment

Outdoor-Air Processing Unit (Discharge Air Temperature Control Type)

FXMQ-MF Series


Combine fresh air treatment and air conditioning, supplied from a single system.



Fresh air treatment and air conditioning can be achieved with a single system. VRV indoor units for air conditioning and an outdoor-air processing unit can be connected to the same refrigerant line.

Lineup

Model Name	FXMQ125MFV7	FXMQ200MFV7	FXMQ250MFV7
Capacity index	125	200	250
Airflow rate	1,080 m ³ /h	1,680 m ³ /h	2,100 m ³ /h




Connection Conditions

- Outdoor-air processing units can be used without indoor units. The total connection capacity index must be 50% to 100% of the capacity index of the outdoor units.
- When outdoor-air processing units and standard indoor units are combined, the total connection capacity index of the outdoor-air processing units must not exceed 30% of the capacity index of the outdoor units. Because connection is possible depending on conditions even when the capacity index of outdoor-air processing units exceeds 30% of the capacity index of the outdoor units, contact your local distributor.


Outdoor-air processing / Discharge air temperature control

The unit supplies outdoor fresh air controlling discharge air temperature from the unit.



- * The default setting of the discharge air temperature is 18°C for cooling operation, and 25°C for heating operation.
- * While in unit protection mode and depending on outdoor air conditions, discharge air temperature may not be at the set temperature.
- * The fan stops in defrosting, oil returning and hot start operations due to mechanical protection control.

Operation range



Applicable to outdoor air temperature range from -5 to 43°C. In cooling operation, 19 to 43°C is adoptable.

- Notes:
1. The operation range shown in the graph is under the following conditions. Equivalent piping length: 7.5 m, Height difference: 0 m.
 2. The system will not operate in fan mode when the outdoor air temperature is 5°C or below.

Precautions for use of FXMQ-MF series

1. This unit is intended for the treatment of outdoor air only. Not to be used for maintaining indoor air temperature. Be sure that the discharge airflow will not blow on people directly.
2. Group control of the product and standard indoor units is not supported. A separate remote controller should be connected to individual unit.
3. If the unit is utilised to operate 24 hours a day, maintenance (part replacement, etc.) must be performed periodically.
4. Temperature setting and Power Proportional Distribution (PPD) are not possible even if the intelligent Touch Controller or the intelligent Touch Manager is installed.
5. The remote controller wired to the outdoor-air processing unit must not be set as the master remote controller. Otherwise, when set to "Auto," the operation mode will switch according to the outdoor air conditions, regardless of the indoor temperature.

Specifications

Type		Ceiling Mounted Duct Type		
MODEL		FXMQ125MFV7	FXMQ200MFV7	FXMQ250MFV7
Power supply		1-phase 220-240 V, 50 Hz		
Cooling capacity *1	Btu/h	47,800	76,400	95,500
	kW	14.0	22.4	28.0
Power consumption		kW	0.359	0.548
Casing		Galvanised steel plate		
Dimensions (H × W × D)		mm	470 × 744 × 1,100	470 × 1,380 × 1,100
Fan	Motor output	kW	0.380	
	Airflow rate	m ³ /min	18	28
		cfm	635	988
External static pressure	220 V/240 V	Pa	185/225	225/275
Air filter		*2		
Refrigerant piping	Liquid	mm	φ 9.5 (Flare)	
	Gas	mm	φ 15.9 (Flare)	φ 19.1 (Brazing)
	Drain	mm	PS1B female thread	
Machine weight		kg	86	123
Sound level *3		220 V/240 V	dB(A)	42/43
Connectable outdoor units *4			6 HP and above	8 HP and above
Operation range (Fan mode operation between 15 and 19°C)			19 to 43°C	
Range of the discharge temperature *5			13 to 25°C	

Notes: *1. Specifications are based on the following conditions:

- Cooling: Outdoor temp. of 33°CDB, 28°CWB (68% RH), and discharge temp. of 18°CDB.
- Equivalent reference piping length: 7.5 m (0 m horizontal)

*2. An intake filter is not supplied, so be sure to install the optional long-life filter or high-efficiency filter.

*3. Anechoic chamber conversion value, measured at a point 1.5 m downward from the unit centre.

These values are normally somewhat higher during actual operation as a result of ambient conditions.

*4. It is possible to connect to the outdoor unit if the total capacity of the indoor units is 50% to 100% of the capacity index of the outdoor unit.

*5. Local setting mode is not displayed on the remote controller.

• This equipment cannot be incorporated into the remote group control of the VRV system.

Options

MODEL		FXMQ125MFV7	FXMQ200MFV7	FXMQ250MFV7
Operation/control	Operation remote controller	BRC1H63W(K) / BRC1E63 / BRC2E61		
	Central remote controller	DCS302CA61		
	Unified ON/OFF controller	DCS301BA61		
	Schedule timer	DST301BA61		
Wiring adaptor for electrical appendices (2)		KRP4AA51		
Filters	Long-life replacement filter	KAF371N140	KAF371N280	
	High-efficiency filter	Colourimetric method 65%	KAF372M140	KAF372M280
		Colourimetric method 90%	KAF373M140	KAF373M280
	Filter chamber *	KDJ3705L140	KDJ3705L280	
Streamer duct chamber		BDEZ500A140VE	BDEZ500A510VE	
Drain pump kit		KDU30L250VE		
Adaptor for wiring		KRP1B61		

Notes: * Filter chamber has a suction-type flange. (Main unit does not.)

- Dimensions and weight of the equipment may vary depending on the options used.
- Some options may not be usable due to the equipment installation conditions, so please confirm prior to ordering.
- Some options may not be used in combination.
- Operating sound may increase somewhat depending on the options used.

Air Treatment Equipment


Outdoor-Air Processing Unit (Room Temperature Control Type)

New FXMQ-BF Series

Improve IAQ with fresh air ventilation and precise room temperature control



Fresh air treatment and air conditioning can be achieved with a single system. **VRV** indoor units for air conditioning and an outdoor-air processing unit can be connected to the same refrigerant line.



Lineup

Model Name	FXMQ80BFV24	FXMQ140BFV24	FXMQ200BFV24	FXMQ250BFV24
Capacity index	80	140	200	250
Airflow rate	690 m³/h	1,230 m³/h	1,740 m³/h	2,160 m³/h

Type of connected indoor units	Connction ratio	FXMQ-BF connection ratio
FXMQ-BF only		50%-130%
Mixed combination (FXMQ-BF and standard VRV indoor units)	120%-130%	≤10%
	110%-120%	≤20%
	100%-110%	≤30%
	50%-100%	≤40%


$$\text{Connection ratio} = \frac{\text{Total capacity index of the indoor units}}{\text{Capacity index of the outdoor units}}$$

Larger connection ratio

Maximum connection ratio increased from 100% to 130%.
When outdoor-air processing units and standard **VRV** indoor units are combined, the total connection capacity index of the outdoor-air processing units must not exceed 40% of the capacity index of the outdoor units.

Outdoor-air processing / Room temperature control

The unit improves IAQ with fresh air ventilation and precise room temperature control.



Set point temperature can be selected similar to standard **VRV** indoor unit. Maintains comfortability and precise temperature control in large areas with the remote sensor option BRC501A-6.

- * This unit cannot be used to handle internal heat loads.
- * The discharge air temperature changes depending on the air conditioning load, outside air temperature, and operation of the protective device.
When the protection function is activated, unprocessed outside air maybe sent directly.
- * The fan stops in defrosting, oil returning and hot start operations due to mechanical protection control.


3-step airflow control

Control of the airflow rate has been improved from 1-step to 3-step control, which enhance usage and design flexibility.

Slim & compact design

Only 300 mm in height and 700 mm in depth, the new casing comes with smaller footprint and with 59% reduction* in unit size.


* Reduction in size compared to conventional FXMQ200/250MF series



Lower power consumption

The change from AC motor to DC motor resulted in lower power consumption and more energy efficiency.

The new FXMQ200BF requires 79% less power consumption making it the perfect choice for small commercial applications.



VRT control

With the VRT* control feature, higher efficiency can be achieved.

* Default setting is VRT off and field setting is required.



New small capacity model

The new 9 kW capacity model is the perfect fit for smaller business such as small/medium-sized shops and convenience stores.

Adjustable external static pressure



Using a DC fan motor, the external static pressure can be controlled within a range of 50 Pa to 200 Pa.

Adjustable external static pressure

50 Pa to 200 Pa

"Airflow rate auto adjustment function" at field setting (local setting by remote controller)

*This function can only be set via wired remote controller.



- <Mechanism>
1. During field setting, power input of DC fan is detected.
 2. External static pressure is estimated from power input of DC fan because PCB of FXMQ-BF has table of external static pressure vs. power input of DC fan.
 3. Actual duct resistance is calculated according to 1 and 2.
 4. Fan speed is automatically adjusted to produce rated airflow.


Notes: "Airflow rate auto adjustment function" can be adjusted within ±10% of rated airflow. (Refer to Engineering Data Book for details)
"Airflow rate auto adjustment function" should be used at field setting only.

Air Treatment Equipment

Outdoor-Air Processing Unit (Room Temperature Control Type)

Extended operation range

The outdoor operation temperature range extended from 19 to 15°CDB*. This enables reliable operation even under wider temperature conditions.



Extended operation range:
Cooling: 15°CDB to 43°CDB

* Thermo-off (fan) operation starts automatically when cooling 19°CDB or less. Operation range can be extended to 15°CDB by field setting.

High efficiency filter (MERV8/MERV14) (Option)

The filter options of MERV8 and MERV14 are available. The high efficiency filter can help remove infectious aerosol in the air.



MERV8 filter



MERV14 filter

Specifications

Model		FXMQ80BFV24	FXMQ140BFV24	FXMQ200BFV24	FXMQ250BFV24
Power supply		1 phase, 220 V, 50 Hz			
Cooling capacity *1	Btu/h	30,700	54,600	76,400	95,500
	kW	9.0	16.0	22.4	28.0
Power consumption		0.080	0.100	0.115	0.180
Casing		Galvanised steel plate			
Dimensions (HxWxD)		mm	300x700x700	300x1,000x700	300x1,400x700
Fan	Motor output	kW	0.140	0.350	
	Airflow rate (H/M/L)	m³/min	11.5/8.6/5.8	20.5/15.4/10.3	29.0/21.8/14.5
		cfm	406/304/205	724/544/364	1,024/770/512
External static pressure		Pa	Rated 100 (200-50)		
Air filter		*2			
Refrigerant piping	Liquid	φ 9.5 (Flare)			
	Gas	φ 15.9 (Flare)		φ 19.1 (Brazing)	φ 22.2 (Brazing)
	Drain	VP25 (External dia. 32, Internal dia. 25)			
Machine weight		kg	29	37	47
Sound level (H/M/L) *3		dB(A)	37.5/30/23	41/34/25	42/35/26
Operation range *4		°CDB	15 to 43		

Notes:

- *1. The capacity is the maximum value under the following conditions:
 - Cooling: Indoor temp. of 33°CDB, 28°CWB, Outdoor temp. of 33°CDB.
 - Equivalent reference piping length: 7.5 m (0 m horizontal)
 - The rated external static pressure and air volume are set in 0.

*2. An intake filter is not supplied, so be sure to install the optional filter.

*3. Anechoic chamber conversion value, measured at a point 1.5 m downward from the unit centre. These values are normally somewhat higher during actual operation as a result of ambient conditions.

*4. The operation range can be extended to 15°C by field setting. When fresh air intake mode is enabled, operation range cannot be extended. (limit at 19 to 43°C)

Options

Model		FXMQ80BFV24	FXMQ140BFV24	FXMQ200BFV24	FXMQ250BFV24
Operation/Control	Wired remote controller	BRC1H63W(K) / BRC1E63 / BRC2E61			
	Wireless remote controller	BRC4C66			
	Remote sensor (for indoor temperature)	BRC501A-6			
	Central remote controller	DCS302CA61			
	Unified ON/OFF controller	DCS301BA61			
	Schedule timer	DST301BA61			
	Filters	MERV8 filter	BAF376B56	BAF376B80	BAF376B160
MERV14 filter		BAF377B56	BAF377B80	BAF377B160	
Filter chamber for MERV8/14 filter		KDDF37AB56	KDDF37AB80	KDDF37AB160	
Long life replacement filter		KAF371B56	KAF371B80	KAF371B160	
Streamer duct chamber		BDEZ500A140VE	BDEZ500A140VE BDEZ500A510VE	BDEZ500A510VE	
Service panel		KTBJ25K56F	KTBJ25K80F	KTBJ25K160F	
Air discharge adaptor		KDAJ25K56A	KDAJ25K71A	KDAJ25K140A	
Adaptor for wiring (operation status output)		★ BRP11B62			
Wiring adaptor for electrical appendices (1)		★ KRP2A61			
Wiring adaptor for electrical appendices (2)		★ KRP4AA51			
Installation box for adaptor PCB ☆ *1		★ KRP4A96 *2,3			
External control adaptor for outdoor unit		★ DTA104A61			
Adaptor for multi tenant (24V type)		★ DTA114A61			
Multi tenant unit for indoor (24V free type)		★ BRP114A61			
Multi tenant unit Booster (24V free type)		★ BRP114A63			
Digital input adaptor for hotel application		★ BRP7A53			

Notes:

*1. Installation Box ☆ is necessary for each adaptor marked ★.

*2. Up to 2 adaptors can be fixed for each installation box.

*3. Only one installation box can be installed for each indoor unit.

Air Treatment Equipment

Heat Reclaim Ventilator with DX-coil


VKM-GC Series

Air quality improvement by introducing fresh outdoor air in the room



Lineup

Model	VKM50GCVE	VKM80GCVE	VKM100GCVE
Capacity Index	31.25	50	62.5
Airflow rate	500 m³/h	750 m³/h	950 m³/h



■ IAQ improvement by fresh air


Maintains comfortable indoor air quality (IAQ) by adding fresh outdoor air having nearly the same temperature and humidity conditions as the indoor air.

This energy-saving heat reclaim ventilator further reduces air conditioning load.

■ Heat reclaim ventilator + Heat exchanger → Comfortable air supply



Equipped with a heat reclaim ventilator and a heat exchanger, the new VKM series minimizes room temperature fluctuations.

The supply air is cooled from 29°C to 17.2°C with DX-coil.



■ Equipped with DC fan motor

- Energy saving: Power consumption reduced by up to 51% (Class 50)
- Flexible installation due to high external static pressure: Increase of up to +50 Pa (Class 80)



■ Supports both 50/60 Hz power supply

Current model 1-phase, 220-240 V, 50 Hz only

New model 1-phase, 220-240 V, 50 Hz
1-phase, 220 V, 60 Hz

■ CO2 sensor control (Option) * Refer to page 185 for details.

When CO2 sensor is installed, it detects the concentration of CO2 in the indoor air and the ventilation rate is controlled appropriately, reducing the air conditioning load due to ventilation.

■ PM2.5 filter (Option) * Refer to page 186 - 188 for details.

Removes PM2.5 particulate matter present in the outdoor air, as well as sulfur oxides and nitrogen oxides, providing clean fresh air to the indoor ambient.


- PM2.5 filter: Removes 99% or more of 2.5 µm particulate matter.
- Activated Carbon filter: Removes sulfur oxides and nitrogen oxides

■ Other characteristics

- Nighttime free cooling operation * Refer to page 182 for details.
- Stainless drain pan
- High-efficiency filter (Option)

Air Treatment Equipment

A compact unit packed with Daikin's cutting-edge technologies.




Specifications

MODEL			VKM50GCVE	VKM80GCVE	VKM100GCVE
Refrigerant			R-410A		
Power Supply			1-phase, 220-240 V/220 V, 50/60 Hz		
Airflow Rate & External Static Pressure (Ultra-high / High / Low) (Note 4)	Airflow	m ³ /h	500/500/440	750/750/640	950/950/820
	Static pressure	Pa	210/170/140	220/180/125	170/120/90
Power Consumption (Ultra-high / High / Low)	Heat exchange mode	W	270/230/170	390/335/220	440/370/260
	Bypass mode	W	305/260/200	390/335/220	440/370/260
Fan Type			Sirocco Fan		
Motor Output			kW		
			0.21×2		
Sound Level (Note 3) (Ultra-high / High / Low)	Heat exchange mode	dB	43/40.5/39	41.5/39/37	41/39/36.5
	Bypass mode	dB	43/41/39	41.5/39/37	41/39/36.5
Temp. Exchange Efficiency (Ultra-high / High / Low)			%		
			76/76/77.5		
Enthalpy Exchange Efficiency (Ultra-high / High / Low)	Cooling	%	64/64/67	66/66/68	62/62/66
	Heating	%	67/67/69	71/71/73	65/65/69
Heat Exchanging System			Air to Air Cross Flow Total Heat (Sensible + Latent Heat) Exchange		
Heat Exchanger Element			Specially Processed Non flammable Paper		
Air Filter			Multidirectional Fibrous Fleeces		
DX-coil Capacity (Cooling / Heating) (Note 1) (Note 2)			kW		
			2.8 / 3.2		
Dimensions (Height×Width×Depth)			mm		
			387 × 1,764 × 832		
Piping Connection	Liquid	mm	φ 6.4 (Flare)		
	Gas	mm	φ 12.7 (Flare)		
	Drain		PT3/4 External Thread		
Machine Weight			kg		
			92		
Unit Ambient Condition	Around Unit		0°C–40°CDB, 80%RH or less		
	OA (Note 5)		-15°C–40°CDB, 80%RH or less		
	RA (Note 5)		0°C–40°CDB, 80%RH or less		

- Notes: 1. Indoor temperature: 27°CDB, 19°CWB, Outdoor temperature: 35°CDB
 2. Indoor temperature: 20°CDB, Outdoor temperature: 7°CDB, 6°CWB
 3. The operating sound measured at the point 1.5 m below the centre of the unit is converted to that measured in an anechoic chamber built in accordance with the JIS C 1502 conditions. The actual operating sound varies depending on the surrounding conditions (near running unit's sound, reflected sound and so on) and is normally higher than this value.
 For operation in a quiet room, it is required to take measures to lower the sound.
 For details, refer to the Engineering Data.
 4. Airflow rate can be changed over to Low mode or High mode.
 5. OA: fresh air from outdoor. RA: return air from room.
 6. Temperature exchange efficiency is the mean value for Cooling and Heating. Efficiency is measured under the following condition: Ratio of rated external static pressure outdoor to indoor is kept constant at 7 to 1.

Air conditioning and outdoor air processing can be accomplished using a single system.



- When the VKM series units are connected, the total connection capacity index must be 50% to 130% of the capacity index of the outdoor units.

Options

Item	Type	VKM50GCVE	VKM80GCVE	VKM100GCVE
Controlling device	Remote controller *1	BRC1H63W(K) / BRC1E63		
	PCB Adaptor	KRP2A61		
	Wiring adaptor for electrical appendices For heater control kit	BRP4A50A		
Additional function	Silencer	—	KDDM24B100	
	Nominal pipe diameter	mm	φ 250	
	High efficiency filter		KAF242J80M	KAF242J100M
	Air filter for replacement		KAF241G80M	KAF241G100M
Flexible duct	1 m	K-FDS201E	K-FDS251E	
	2 m	K-FDS202D	K-FDS252E	
CO ₂ Sensor		BRYC24B50M	BRYC24B100M	
PM2.5 filtration unit *2		BAF249A500	BAF249A20A	
PM2.5 with activated carbon filtration unit *2		BAF249A500C	BAF249A20AC	
Streamer duct chamber		BDEZ500A60VE	BDEZ500A140VE	
		BDEZ500A140VE		

*1. Necessary when operating a Heat Reclaim Ventilator (VKM) independently. When operating interlocked with other air conditioners, use the remote controllers of the air conditioners.

*2. Refer to pages 186 - 188 for details.

Please inquire concerning optional accessories not listed above.

Air Treatment Equipment

Heat Reclaim Ventilator

VAM-H Series

Daikin VAM series ensures fresh air intake and energy savings



Lineup		
VAM150HVE	VAM250HVE	VAM350HVE
VAM500HVE	VAM650HVE	VAM800HVE
VAM1000HVE	VAM1500HVE	VAM2000HVE

Airflow rate: 150-2,000 m³/h



BRC1H63W

BRC1H63K


New features

Design flexibility

By significantly improving external static pressure, support for a variety of duct layouts is possible, and installation flexibility has been improved.

The 1000-2000 class model has become more compact, and ease of installation has improved.


Comparison of external static pressure



Improvement of installation workability

Improved workability by changing dimensions and shape of lifting lug

The structure that prevents nut slippage eliminates the need to replace the lifting lug even when installed upside down.




Energy saving

Sensing sensor stop mode

In situation of no human occupancy is detected, the operation is turned off.

When the "Sensing sensor" installed on the air conditioner detects no occupancy in the room, the ventilation system and air conditioner system is turned off automatically to reduce energy wastage.



* During group controlling of air conditioner, no occupancy stop mode cannot be used.


* During 24-hours ventilation mode is turned on, the normal operation mode is changed to 24-hours ventilation mode.

* Once the absence is detected and stopped, the operation will not be performed automatically again.

Humidity sensor (Option)

A humidity sensor (option) can be installed for greater comfort and energy-saving ventilation.

Conditions of low temperature and high humidity... Example, a rainy day, etc.




Stylish remote controller

NEW Stylish Remote Controller BRC1H63W (K) combining many VAM-dedicated functions

- Sensor results can be displayed up to 3 item on the information screen.
- Sensor results can be shared to the remote controller group.
- New icons such as 24-Hour Ventilating, Fresh Up, Nighttime Free Cooling Operation (Night Purge) have been added to the Information screen.

Sensor view of the Information screen



Note:
3 items selected by remote controller setting.

Air Treatment Equipment

Heat Reclaim Ventilator

Energy saving / Heat recovery functions

Air conditioner and ventilation system can be interlocked to provide even greater comfort and energy saving.


The system can be interlocked with Daikin air conditioners to provide energy saving ventilation solution for various situation.



Pre-cool, Pre-heat control

Intentional delay of the start-up time


When the air conditioner is started up, the ventilation start-up is delayed to reduce load caused by the outside air. This reduces power consumption of air conditioners.



Auto-ventilation mode changeover switching

Automatically determine the appropriate ventilation for each situation


Indoor temperature and the outdoor temperature are detected, and the system automatically switches to the ventilation mode which has higher energy-saving effect.



Nighttime free cooling operation

Efficient use of outdoor air at night.

Rise in indoor temperature is avoided by automatically cooling the outdoor air at night, thus reducing air conditioning load at the start of cooling operation on the next morning.



CO₂ sensor control (Option) *Refer to pages 185 for details.

When CO₂ sensor is installed, it detects the concentration of CO₂ in the indoor air and the Ventilation rate is controlled appropriately, reducing the air conditioning load due to ventilation.

Improvement of IEQ (Indoor Environmental Quality)


PM2.5 filter (Option) *Refer to pages 186 - 188 for details.

Removes PM2.5 particulate matter present in the outdoor air, as well as sulfur oxides and nitrogen oxides, providing clean fresh air to the indoor ambient.

- PM2.5 filter: Removes 99% or more of 2.5 μm particulate matter.
- Activated Carbon filter: Removes sulfur oxides and nitrogen oxides.

Fresh Air Comfort

Round Flow Cassette indoor units can be connected to a duct to provide fresh outdoor air for comfortable air from the air conditioner. Installation is also possible for existing indoor units.



- 1 Heat Reclaim Ventilator
- + Round Flow Cassette (including with sensing type)

Nighttime conditioning

Air Treatment Equipment




Heat Reclaim Ventilator

Specifications

Model			VAM150HVE	VAM250HVE	VAM350HVE	VAM500HVE	VAM650HVE	VAM800HVE	VAM1000HVE	VAM1500HVE	VAM2000HVE									
Power Supply			Single phase, 220-240 V/220 V, 50/60 Hz																	
Temperature exchange efficiency (50/60 Hz)	For Cooling	Ultra-High	66.0/66.0	60.5/60.5	65.0/65.0	61.5/61.5	59.5/59.5	61.5/61.5	58.0/58.0	61.5/61.5	58.5/58.5									
		High	66.0/66.0	60.5/60.5	65.0/65.0	61.5/61.5	59.5/59.5	61.5/61.5	58.0/58.0	61.5/61.5	58.5/58.5									
		Low	69.0/69.5	65.0/65.5	70.0/70.0	63.0/64.0	62.5/63.0	64.0/65.0	61.5/62.0	65.5/66.0	65.5/65.5									
Enthalpy exchange efficiency (50/60 Hz)	For Cooling	Ultra-High	63.5/63.5	60.0/60.0	62.5/62.5	62.5/62.5	60.0/60.0	63.0/63.0	60.0/60.0	63.0/63.0	60.0/60.0									
		High	63.5/63.5	60.0/60.0	62.5/62.5	62.5/62.5	60.0/60.0	63.0/63.0	60.0/60.0	63.0/63.0	60.0/60.0									
		Low	66.0/66.5	61.5/62.0	64.5/65.0	64.0/65.0	62.5/63.0	64.5/65.5	62.0/62.5	65.5/66.0	64.5/64.5									
Power Consumption (50/60 Hz)	Heat exchange mode	Ultra-High	96-103/132	126-141/172	178-193/231	296-326/390	381-426/472	664-684/829	683-736/883	1,274-1,353/1,645	1,365-1,471/1,763									
		High	90-93/118	114-123/144	163-170/207	248-261/329	307-319/413	603-612/712	621-656/763	1,207-1,225/1,423	1,241-1,311/1,526									
		Low	68-73/67	75-83/79	132-142/145	223-233/268	264-276/332	504-544/562	539-569/594	1,008-1,089/1,125	1,079-1,138/1,188									
	Bypass mode	Ultra-High	96-103/132	126-141/172	178-193/231	296-326/390	381-426/472	664-684/829	683-736/883	1,274-1,353/1,645	1,365-1,471/1,763									
		High	90-93/118	114-123/144	163-170/207	248-261/329	307-319/413	603-612/712	621-656/763	1,207-1,225/1,423	1,241-1,311/1,526									
		Low	68-73/67	75-83/79	132-142/145	223-233/268	264-276/332	504-544/562	539-569/594	1,008-1,089/1,125	1,079-1,138/1,188									
Sound Level (50/60 Hz)	Heat exchange mode	Ultra-High	33.0-34.0/34.0	33.0-34.0/33.5	32.0-33.0/34.5	36.0-37.0/38.5	37.5-38.0/38.0	41.5-42.5/41.0	42.0-43.0/42.5	43.0-44.0/44.0	43.5-44.0/44.5									
		High	30.5-32.0/28.0	31.5-32.5/28.0	30.0-31.5/27.5	35.0-36.0/35.0	36.0-36.5/37.0	39.5-41.0/37.0	40.0-41.0/38.0	41.0-42.5/39.0	41.5-43.0/40.0									
		Low	23.0-25.5/20.0	23.0-25.5/21.0	26.5-28.5/22.0	32.0-34.0/31.0	34.0-35.0/32.5	36.0-38.5/33.0	38.0-39.5/34.5	38.0-40.5/35.0	39.0-41.0/36.5									
	Bypass mode	Ultra-High	33.5-34.0/36.0	33.0-34.0/34.5	32.5-33.5/34.5	36.0-37.0/38.5	39.5-40.0/42.0	41.5-42.5/41.0	42.0-43.0/42.5	43.0-44.0/44.0	43.5-44.0/44.5									
		High	31.5-33.0/28.5	31.0-32.5/29.0	31.0-32.0/27.5	35.0-36.0/35.0	38.0-38.5/39.0	39.5-41.0/37.0	40.0-41.0/38.0	41.0-42.5/39.0	41.5-43.0/40.0									
		Low	23.0-25.5/20.5	23.5-25.5/21.5	27.0-29.0/23.0	32.0-34.0/31.0	35.5-36.5/33.5	36.0-38.5/33.0	38.0-39.5/34.5	38.0-40.5/35.0	39.0-41.0/36.5									
Casing			Galvanised steel plate																	
Insulation Material			Self-extinguishable polyurethane foam																	
Dimensions (H x W x D)			mm 278 x 551 x 810			306 x 800 x 879			338 x 832 x 973			387 x 1,012 x 1,110			785 x 1,012 x 1,110					
Machine Weight			kg 22			31			41			43			63			133		
Heat Exchange System			Specially processed nonflammable paper																	
Heat Exchange Element Material			Multidirectional fibrous fleeces																	
Fan	Type		Sirocco fan																	
	Airflow Rate (50/60 Hz)	Ultra-High	150/150	250/250	350/350	500/500	650/650	800/800	1,000/1,000	1,500/1,500	2,000/2,000									
		High	150/150	250/250	350/350	500/500	650/650	800/800	1,000/1,000	1,500/1,500	2,000/2,000									
		Low	100/80	165/145	275/235	470/420	570/495	720/610	880/835	1,350/1,250	1,650/1,580									
	External static pressure (50/60 Hz)	Ultra-High	125-140/155	115-130/135	170-185/230	165-190/245	185-190/260	210-235/250	205-225/220	195-215/235	190-210/210									
		High	100-120/100	80-90/60	145-165/80	140-175/180	140-155/210	170-215/140	155-195/100	150-180/125	140-180/85									
Low		44-80/28	35-75/20	90-102/36	124-155/127	108-119/122	138-174/81	115-150/70	123-146/88	96-123/53										
Motor Output		kW 0.030 x 2			0.060 x 2			0.100 x 2			0.170 x 2			0.190 x 2						
Effective ventilation rate			Ultra-High % 90																	
Connection duct diameter			Indoor side	mm φ100			φ150			φ200			φ250			φ250 x 4				
			Outdoor side	mm □ (680 x 290) x 2																
Unit ambient condition			-15°C to 50°CDB, 80%RH or less																	

- Notes:
- Airflow rate can be changed over to Low mode or High mode.
 - Temperature Exchange Efficiency is the mean value between cooling and heating.
 - Efficiency is measured under the following conditions: Ratio of rated external static pressure has been maintained as follows; outdoor side to indoor side = 7 to 1.
 - In conformance with JIS standards (JIS B 8628), operating sound level is based on the value when one unit is operated, with the value converted for an anechoic chamber. This is transmission sound from the main unit, and does not include sound from the discharge grille. Thus it is normal for the sound to be louder than the indicated value when the unit is actually installed.

Remote controller function for Heat Reclaim Ventilator

Function	Detail	BRC1H63W(K)	BRC1E63	BRC2E61
				
Air conditioner interlock	Interlock Heat Reclaim Ventilator with air conditioner by one remote controller	●	●	●
Ventilation mode	Switch the ventilation mode (Automatic, Heat exchange, Bypass)	●	●	—
Ventilation airflow rate	When using CO ₂ sensor, ventilation volume can be changed	●	●	●
Fresh up indication	Indicates that fresh up operation is being carried out	●	—	—
CO ₂ indication	Indicates value of CO ₂ sensor	○	—	—
Outdoor temperature indication	Indicates outdoor air temperature (OA)	○	—	—
Nighttime free cooling indication	Indicates that night purge operation is set	○	—	—
24 hour ventilating indication	Indicates that 24 hour ventilating operation is set	○	—	—
Ventilating operation indication	Indicates that ventilating operation is being carried out even when night purge operation and 24 hour ventilating operation is being carried out	●	●	—
Ventilating standby indication	Indicates that ventilating operation has been stopped temporarily during pre-cool / pre-heat control	○	—	—
Sharing CO ₂ data	Share the CO ₂ data to submit from main unit with in the group	○	—	—

○ : New functions / ● : Installed functions


Options

Item	MODEL	VAM150HVE	VAM250HVE	VAM350HVE	VAM500HVE	VAM650HVE	VAM800HVE	VAM1000HVE	VAM1500HVE	VAM2000HVE		
Additional function	Silencer	—										
	Nominal pipe mm	KDDM24B100										
	High efficiency filter	φ200										
Air filter for replacement		KAF242J25M			KAF242J50M			KAF242J65M			KAF242K100M	
		KAF241L25M			KAF241L35M			KAF241L65M			KAF241L100M	
Flexible duct (1m)		K-FDS101E			K-FDS151E			K-FDS201E			K-FDS251E	
Flexible duct (2m)		K-FDS102E			K-FDS152E			K-FDS202E			K-FDS252E	
CO ₂ sensor*2		BRYC24A25M			BRYC24A35M			BRYC24A65M			BRYC24A100M	
Humidity sensor		BRYH241A100 (for RA) / BRYH242A100 (for OA)										
PM2.5 filtration unit*3		BAF249A150	BAF249A300	BAF249A350	BAF249A500	—				BAF429A20A		
PM2.5 with activated carbon filtration unit*3		BAF249A150C	BAF249A300C	BAF249A350C	BAF249A500C	—				BAF429A20AC		
Streamer duct chamber		BDEZ500A60VE			BDEZ500A140VE			BDEZ500A140VE			BDEZ500A510VE	
Wired remote controller		BRC1H63W (White) / BRC1H63K (Black) / BRC1E63 / BRC2E61										
Centralised controlling device	Residential central remote controller	DCS303A51*1										
	Central remote controller	DCS302CA61										
	Unified ON/OFF controller	DCS301BA61										
	Schedule timer	DST301BA61										
PCB Adaptor	Wiring adaptor for electrical appendices	KRP2A62										
	Installation box for adaptor PCB	KRP1C18A90										
	For heater control kit PCB adaptor for wiring	BRP4A50A KRP1C18										

- Notes: *1. For residential use only. When connect with a Heat Reclaim Ventilator (VAM), you can only switch the power ON/OFF. It cannot be used with other central control equipment.
*2. Refer to pages 185 for details. *3. Refer to pages 186 - 188 for details.

PCB adaptor for heater control kit [BRP4A50A] (Option)

When the installation of an electric heater is required in a cold region, this adaptor with an internal timer function eliminates the complicated timer connecting work that was necessary with conventional heaters.




- Notes when installing :
- Examine fully an installation place and specification for using the electric heater based on the standard and regulation of each country.
 - Supply the electric heater and safety production devices such as a relay and a thermostat, etc of which qualities satisfy the standard and regulation of each country at site.
 - Use a non-inflammable connecting duct to the electric heater. Be sure to use 2 m or more between the electric heater and the Heat Reclaim Ventilator for safety.
 - For the Heat Reclaim Ventilator, use a different power supply from that of the electric heater and install a circuit breaker for each.

Air Treatment Equipment

Airflow rate control with CO₂ sensor (Option) for VAM / VKM series

The CO₂ sensor controls airflow rate so that it best matches the changes of CO₂ level in the room. This prevents energy losses from over-ventilation while maintaining indoor air quality with optional CO₂ sensor.

● Example of CO₂ sensor operation in an office room:



PM2.5 filtration unit (Option) for VAM / VKM series

Rapid urbanization has increased industrial and automobile emissions, resulting in higher PM2.5 levels. This has become the source of respiratory diseases and poses a serious threat to a long term health issue. As the air quality has worsened, research has shown the harmful effects of PM2.5 on the health of the general public.

Double-layered efficient filtration


PM2.5 filters are double-layered.

1. The front filter effectively removes large particles.
2. The PM2.5 filter layer contains a large amount of static electricity to capture particulate matter efficiently.



Filtering PM2.5 efficiently for healthier and more comfortable environments

This filter removes 99% or more of 2.5 μm particulate matter.




*Test results by the Heating, Ventilation and Air Conditioning Lab at Tongji University
Test environment: temperature 25-26°CDB, humidity 58-60%RH

Air Treatment Equipment


Electrostatic dust collection filter: more efficient and longer lasting effect

The PM2.5 filter layer contains a large amount of static electricity to capture particulate matter efficiently, including those smaller than the grid mesh. The filter is difficult to be blocked by particles and has good ventilation and long life span.

Daikin Electrostatic Dust Collecting Filtration



With the capturing effect of static electricity, particles are adsorbed on the filter fabric.



The filter is not blocked and therefore continuous Supply Air is guaranteed.

Long-lasting highly efficient dust collection capacity


PM2.5 with activated carbon filtration unit (Option) for VAM / VKM series

Extra-high performance filter against sulfur oxides and nitrogen oxides

Effective Use of Active Carbon Material to Enlarge the Adsorption Area

As an expert in the research and development of filters, DAIKIN has specifically selected active carbon material as the main substance to constitute the filter against sulfur oxides and nitrogen oxides. The material's usable pore surface is fully exploited, thus extending the filter's durability.

Notes: Surface area of active carbon: 700 m²/g
Given a newspaper page of 40.6 cm wide by 54.6 cm long, each gram of active carbon has a surface area of 3,000 newspaper pages.




Intelligent Identification, Super-effective Adhesion

The special substance added in the pores of active carbon can exclusively target sulfur oxide and nitrogen oxide gases and stick to them without blocking other unidentified gases. This ensures long durability of the filter.

Note: The figures are based on in-house tests under the following lab conditions: temperature 22 to 25°CDB, humidity 35 to 40% RH, air flow rate 0.2 m/s.

Unidentified Gases



Specifications

PM2.5 filtration unit

MODEL		BAF249A150	BAF249A300	BAF249A350	BAF249A500	BAF429A20A
Dimensions (H x W x D)	mm	220x603x366	220x603x366	300x623x366	300x623x366	470x971x370
Connection Duct Diameter	mm	φ 100	φ 150	φ 150	φ 200	580x348
Airflow Rate	m ³ /h	150	250	350	500	2,100
PM2.5 Filter	Initial Pressure Drop	Pa	34	30	31	42
	Filter Lifetime ^{*1}		1 year			
	Filtration Efficiency ^{*2}		99% or higher			
	Filter Material No. ^{*3}		BAF244A300		BAF244A500	BAF424A20A

Notes: 1. Annual usage: 400 hrs/month x 12 months = 4,800 hrs
2. 99% or higher removal rate of ultra-fine particles with diameters of 2.5 μm or more.
3. Filters come with applicable filtration units with a one-year life. They can be purchased and replaced according to their model numbers.

PM2.5 with activated carbon filtration unit

MODEL		BAF249A150C	BAF249A300C	BAF249A350C	BAF249A500C	BAF429A20AC
Dimensions (H x W x D)	mm	220x603x366	220x603x366	300x623x366	300x623x366	470x971x370
Connection Duct Diameter	mm	φ 100	φ 150	φ 150	φ 200	580x348
Airflow Rate	m ³ /h	150	250	350	500	2,100
Total Initial Pressure Drop for PM2.5 with Activated Carbon Filtration Unit	Pa	37	35	36	51	less than 50
PM2.5 Filter	Initial Pressure Drop	Pa	34	30	31	42
	Filter Lifetime ^{*1}		1 year			
	Filtration Efficiency ^{*2}		99% or higher			
	Filter Material No. ^{*3}		BAF244A300		BAF244A500	BAF424A20A
Activated Carbon Filter	Initial Pressure Drop	Pa	3	5	5	9
	Filter Lifetime		1 year			
	Filter Material No. ^{*3}		BAF244A300C		BAF244A500C	BAF424A20AC

Notes: 1. Annual usage: 400 hrs / month x 12 months = 4,800 hrs.
2. 99% or higher removal rate of ultra-fine particles with diameters of 2.5 μm or more.
3. Filters come with applicable filtration units with a one-year life. They can be purchased and replaced according to their model numbers.

Control Systems

Individual control systems for VRF systems

Stylish remote controller (Option) New



Special Site



White
BRC1H63W



Black
BRC1H63K

A complete redesigned controller focused to enhance user experience



reddot design award

Sleek and stylish design

- Combines refinement and simplicity
- Echoes the distinct blue circle and simplicity of design
- Two attractive colours to match any interior
- Compact, measures only 85 x 85 mm



User-friendly interface

- Just three buttons and a large-figure display
- Customisable display
- Direct access to basic functions (ON/OFF, Operation mode, Temperature setting, Airflow rate, Airflow direction)
- Timer functions (OFF timer, Weekly schedule timer)
- Simple screen for hotel display



Easy setting via smartphone application using Bluetooth® wireless technology (for Installer/Facility manager)

Keep hotel room comfortable

- Improved setback function by setting the lower temperature limit in cooling and higher temperature in heating mode.
- Window/door contact interlock function is available via optional Digital Input Adaptor BRP7A*.



<App screen image>

Shorter installation time

- Easy to create multiple remote control and field settings via App
- Prepare a setting in advance at the office and immediately send it to the on-site remote controller
- Save and reuse settings
- Remote update function (OTA: Over The Air)

Navigation remote controller (Wired remote controller) (Option)




BRC1E63

A series of user friendly functions that can be individually selected

Energy saving

Setpoint range set

- Avoids excessive cooling by limiting the min. and max. set temperature.
- Convenient for use at a place where any number of people may operate it.



Setpoint auto reset

- Even if the set temperature is changed, the new set temperature returns to the previous preset value after a preset duration of time.
- Period selectable from 30, 60, 90, or 120 min.



Off timer

- Period can be preset from 30 to 180 minutes in 10-minute increments.


Convenience

Setback (default: OFF)

- Maintains the room temperature in a specific range during unoccupied period by temporarily starting air conditioner that was turned OFF.

Weekly schedule

- 5 actions per day can be scheduled for each day of the week.
- The holiday function will disable schedule timer for the days that have been set as holiday.
- 3 independent schedules can be set. (e.g. summer, winter, mid-season)



Auto display off

- Period can be preset from 10, 30, 60 minutes, and OFF. Initial setting is 30 minutes.

Comfort

Individual airflow direction

- Airflow direction can be individually adjusted for each air discharge outlet.

5-step airflow control

- Airflow rate can be selected from 5-step control.

Auto airflow rate

- Airflow rate is automatically controlled.

Control Systems

Individual control systems for VRF systems

■ Simplified remote controller (Option)



BRC2E61

Easy operation with new intuitive design

Simple operation

Using only six buttons, users have direct access to basic functions. This enables them to easily set comfort to their preference.

- ON/OFF
- Operation mode
- Temperature setting
- Airflow rate (5-step & Auto)*
- Up and down airflow direction (5-step & Swing)*
- ON/OFF timer

* The number of airflow steps and availability of auto airflow rate and swing mode depend on the type of indoor unit.

Intuitive design

- By using pictograms, the user-friendly interface enables convenient and easy operation.

Compact size

- Measuring only 85 x 85 mm, the new remote controller is extremely compact and complements any interior design.



■ Wireless remote controller (Option)



BRC-M series




Signal receiver unit (Installed type)

- The wireless remote controller is supplied in a set with a signal receiver.
- Signal receiver unit of installed type is contained inside decoration panel or indoor unit.
- Shape of signal receiver unit differs according to the indoor unit.

Note: The signal receiver unit shown in the photograph is for mounting inside the decoration panel of FXF(S)Q series.

- Backlight LCD of new wireless remote controller



Pressing the backlight button helps operating in dark rooms.

- A compact signal receiver unit (separate type) to be mounted into a wall or ceiling is included.



BRC-C, E series



Signal receiver unit (Separate type)


* Wireless remote controller and signal receiver unit are sold as a set except for FXKQ-A series.
* Refer to page 230 for the name of each model.

Wide variation of remote controllers for VRF indoor units

MODEL	FXFTQ	FXFRQ	FXFSQ	FXFQ	FXZQ	FXCQ	FXKQ-A	FXKQ-MA	FXDFQ	FXDBQ	FXDQ	FXSQ	FXMQ	FXHQ	FXAQ	FXL(N)Q	FXVQ	FXB(P)Q
Stylish remote controller (BRC1H63W / BRC1H63K)	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Navigation remote controller (BRC1E63)			●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Simplified remote controller (BRC2E61)				●	●	●		●	●	●	●	●	●	●	●	●	●	●
Wireless remote controller* (Installed type signal receiver unit)			●	●	●	●								●	●			
Wireless remote controller* (Separate type signal receiver unit)								●	●	●	●	●	●			●		●

*Refer to page 230 for the name of each model.


The wired remote controller supports a wide range of control functions



Control Systems

Integrated building monitoring system

The high speed transmission of DIII-NET enables more advanced control of the VRV system, providing you with enhanced comfort.



Control Systems

Advanced control systems for VRV systems



Intelligent Manager
DCM601B51

Various types of equipment in a building can be controlled by a single controller.

One touch selection enables flexible control of equipment in a building.

Individual air-conditioning control

The flexible control achieved by the VRV system precisely meets different air conditioning needs in each room (e.g. offices, conference rooms, hotel rooms).




Lighting control **DALI-compatible**

DALI-compatible LED lighting systems can be controlled and monitored. Lighting control is enhanced through an interlock function with air conditioners and other functions.




Air-conditioning control for large spaces

Air handling units can also be controlled. Large spaces, such as entrance halls and shopping malls, can be easily controlled to ensure comfort.



Building equipment control

Various types of equipment other than air conditioners, including ventilators, fans, and pumps, can also be controlled.



For energy saving & comfort

intelligent Touch Manager maximises the advantages of VRV features


intelligent Touch Manager is an advanced multi-zone controller that provides the most cost-effective way to control and monitor the Daikin VRV system.

The 10.4" LCD touch screen is easy to use with three different screen views to include the floor plan layout view, icon view and list view and menus for system configurations.

It is also easy to use with standardized remote Web Access from your PC.


It can manage a total of 650 management points consisting of up to 512 Daikin indoor unit groups (up to 1024 indoor units) along with building equipment control / monitoring with Digital Inputs / Output (Di/Dio), Analog Inputs / Output (Ai/Ao) and Pulse input (Pi) optional devices.

Schedule the operation time for each application.



Setting the I-demand function and nighttime quiet operation function is also possible.

Turn the unit OFF if a user didn't.



External contact demand control function

This function automatically controls outdoor and indoor unit capacity based on contact signals sent from demand controller (field supply) etc. to save power consumption during peak hours.

- You may set 3 levels that can be switched by ON/OFF signal of 3 contacts
- Control settings are pre-set for each level
- Outdoor unit: I-demand function for peak power limit
- Indoor unit: Set temperature shift, Forced thermostat OFF




Define the setpoint range that users can change.


With Remote controller



With Control System



Reset setpoint regularly.



Control Systems

Lighting control (Option)

In addition to switching lights on and off, advanced lighting control, such as illuminance adjustment, can be achieved

Connection to DALI-compatible lighting control system

DALI-compatible

Please contact your local sales office for details.

Simple wiring (daisy chain) enables management of LED lighting by the *intelligent Touch Manager*. Various air conditioning and lighting control is enabled through the interlock with occupancy sensors and illuminance sensors.


Lighting control achieved by the *intelligent Touch Manager*

[Operation]

- Switch-on/switch-off operation
- Illuminance (1–100%) control
- Various illuminance patterns can be registered
- Registered pattern can be selected from *intelligent Touch Manager*

[Monitoring]

- Switch-on/switch-off status monitoring
- Lighting abnormality monitoring
- Illuminance monitoring
- DALI occupancy sensor monitoring
- DALI illuminance sensor monitoring



Air conditioning and lighting for which power consumption is high can be efficiently controlled to promote energy conservation and cost reduction!


Overview of control

- Up to 5 DALI modules can be connected to a single BACnet® controller.
- Up to 64 DALI LED drivers (64 addresses) can be connected to a single DALI module.
- 64 DALI addresses can be freely assigned to up to 16 groups using a single DALI module. (Each group corresponds to a management point of the *intelligent Touch Manager*.)
- Up to 16 scenes can be set to a single DALI module.
- Up to 12 sensors (occupancy, illuminance) can be connected to a single DALI module.
- DALI BUS simplifies wiring and setting work by daisy chain wiring and automatic address setting.

Easy maintenance and energy saving by lighting control


Case 1

Switch-on / switch-off and illuminance are controlled based on a schedule to cut wasteful power consumption.




Case 2

Occupancy sensors are used to eliminate both wasteful lighting and air conditioning. When a room is unoccupied, the air conditioning stops and the lighting is switched off.



Case 3

Lighting abnormalities (e.g. burned-out bulbs) can be checked on the *intelligent Touch Manager* screen.



The layout screen enables quick identification of specific locations.

Tenant management

Reporting the power consumption of VRV system for each tenant (PPD* Option)

With the PPD function, power consumption can be calculated for each indoor unit (Option)


The energy consumption is proportionally calculated for each indoor unit. The data can be used for energy management and calculation of air conditioning usage fees for respective tenants.

Operational information of individual indoor units are monitored, based on distribution of power consumption of outdoor units.

Daikin's PPD keeps track of power distribution for each indoor unit. It performs air conditioning billing calculations quickly and automatically.

It is easy to output PPD data.

PPD data is output in CSV format to a PC or USB memory device and can be freely processed and managed.



*PPD (Power Proportional Distribution) is Daikin's proprietary calculation method.


Air conditioning bills can be issued by one click (PPD* Option)

Electricity bills can be easily calculated for each tenant (Option)

The power consumption of VRV controlled by the *intelligent Touch Manager* can be easily managed for each tenant using a PC. The electricity bill settings facilitate billing work through easy calculation and issuance of VRV electricity bills.

Main functions

- Register tenants
- Set the electricity unit price for 5 time zones
- Calculate power consumption and electricity charge for each tenant
- Show aggregation results in the specified period for each tenant
- Output the results (Printout and CSV file)



*PPD (Power Proportional Distribution) is Daikin's proprietary calculation method.

Effective service functions offered to tenants

Smartphone will be a remote controller of VRV system (Option)

Users can operate and check the status of VRV system from their smartphones via the internet.


It is not necessary to move where a remote controller is located with this feature.

VRV system in other rooms can be operated, and their status can be checked. It is also possible to check if air conditioners in other rooms remain switched on etc., helping achieve energy saving.

For buildings VRV Smartphone Remote Controller


Up to 1024 indoor units can be controlled.

Just add Smartphone Controller for Office DCPF01 to this system



Control Systems

intelligent Touch Manager system overview




Air conditioning network service system

Preventive maintenance

The *intelligent Touch Manager* can be connected to Daikin's own Air Conditioning Network Service System for remote monitoring and verification of operation status for *VRV* system. By its ability to predict malfunctions, this service provides customers with additional peace of mind.

Enhanced convenience with link to the Air Conditioning Network Service System

The *intelligent Touch Manager* connects seamlessly to Daikin's 24-hour Air Conditioning Network Service System.



Daikin offers a variety of control systems

Convenient controllers that offer more freedom to administrators


Ease of use and expanded control functions

The user-friendly controller features colours, multilingual function, and icons in the display for ease of understanding. A wide variety of control methods can be accommodated, permitting administrators to monitor and operate the system even when they are away from the controller.



Connect VRV system to your BMS via BACnet® or LONWORKS®

Compatible with BACnet® and LONWORKS®, the two leading open network communication protocols, Daikin offers interfaces that provide a seamless connection between *VRV* system and your BMS.




Dedicated interfaces make Daikin air conditioners freely compatible with open networks

Notes: 1. BACnet® is a registered trademark of American Society of Heating, Refrigerating and Air-Conditioning Engineers (ASHRAE).
2. LONWORKS® is a trademark of Echelon Corporation registered in the United States and other countries.

Specialised solution for office, home and hotel with Smartphone Controller Series

Catering to different applications, ranging from 10 indoor units to 2048 indoor units




- For Office Building Automation System
- For Home Smart Home Solution
- For Hotel Air Conditioning Guestroom Interlocking Management



- Smartphone Controller for Office (Touchscreen Controller)
- Smartphone Controller for Office (Controller Extension)
- Smartphone Controller for Office (Multisite Extension)
- Smartphone Controller for Home (Lite Version)
- Smartphone Controller for Hotel
- Smartphone Controller for Resort

Home automation interface adaptor

The **VRV** system can be operated from the home automation system.



Functions Monitor

On/Off	On/Off status of indoor units
Operation mode	Cooling, Heating, Fan, Dry, Auto (depend on indoor unit capability)
Setpoint	Setpoint of indoor units
Room temperature	Suction temperature of indoor units
Fan direction	Swing, Flap direction (depend on indoor unit capability)
Fan volume	L, M, H (depend on indoor unit capability)
Forced off status	Forced off status of indoor units
Error	Malfunction, Warning with Error code
Filter sign	Filter sign of indoor units
Communication status	Communication normal/error of indoor units

Control

On/Off	On/Off control of indoor units
Operation mode	Cooling, Heating, Fan, Dry, Auto (depend on indoor unit capability)
Setpoint	Cooling/Heating setpoint
Fan direction	Swing, Stop, Flap direction (depend on indoor unit capability)
Fan volume	L, M, H (depend on indoor unit capability)
Filter sign reset	Reset filter sign of indoor units

Retrieve system information

Connected indoor units	DIII-NET address of connected indoor units can be retrieved.
Indoor unit capabilities	Indoor unit capabilities such as operation mode, fan control, setpoint HV can be retrieved.


* Modbus® is a registered trademark of Schneider Electric S.A.

Complete control system for VRV systems



Office Air Conditioning Solution (Smartphone Controller for Office :DCPF01 / Smartphone Controller for Office (Touchscreen Controller) :DCPF04)

A simple office buildings air conditioning solution with a secured, cloud enabled platform, allowing greater ease of control and control while being energy-efficient. The flagship model DCPF04 offers the smart control system with a dedicated touch panel.



- Easy to install and configure with dedicated Configuration Mobile App for installers.
- Remote control operation through mobile App from anywhere.
- Energy management through P.P.D. billing, Energy graph and real time energy display function
- IAQ Management via real time monitoring and trend graph for keeping record.
- Effective Air conditioning usage with setpoint range limitation, set back function, remote control prohibition.

Specifications

Category	Function	Description
Monitoring & Control	Status monitoring	On/Off, setpoint, operation mode, fan step, flap, error, error code, Room temperature
	Manual Operation	On/off, setpoint, operation mode, fan step, flap, scene control ¹
	Remote control prohibition	Individually prohibit operation of each local remote-control function
	Setpoint range limitation	To limit setpoint range for each indoor unit management point
Automatic Control functions	Automatic changeover ¹	Number of changeover groups: 100
	Off timer	Off timer duration can set from 5min to 120min with every 5min interval
	Setback ¹	Setback setpoint can selected within 24-35°C in cooling mode and 5-20°C in heating mode.
	Schedule	Number of programmes: 100; Up to 20 actions can be registered per pattern.
Data Management	Interlock ¹	Interlock operation depending on equipment status
	History, Report ¹	Operation data (latest information and operation report) and error report on daily/monthly basis.
	Trend graph ¹ , energy graph ¹	Chart on environmental changes and energy (and other meter) values.
P.P.D Billing ^{1,2}	Real time energy display ^{1,2}	Daily/ Monthly real time energy consumption status on screen.
System Setting	Generate Bill with Power Proportional Distribution data retrieved from the system.	Language, Password setting, Account setting, Notification, Email Notification

¹ Optional software for Smartphone Controller for Office, DCPF01


² Optional software for Smartphone Controller for Office (Touchscreen Controller), DCPF04

Control Systems

Office Expanded Solution (Smartphone Controller for Office (Controller Extension) :DCPF05)

A dedicated control solution for large scale office buildings through centralised control of multiple Smartphone Controller for Office controller on a single secured and cloud-enabled platform.


Note: P.P.D. & Tenant Billing Management and Real-Time Energy Monitoring (R.E.M.) are offered as optional software.



Multi Site Management Solution (Smartphone Controller for Office (Multisite Extension) :DCPF10)

Centralised control and remote access for all devices in multiple buildings across different locations conveniently located on one secured platform.

Note: Multi-site Branch Expansion is offered as optional software.




Smart Home Solution (Smartphone Controller for Home :DCPH01)

The complete smart home air conditioning solution for every homeowners with integration capabilities to allow ease and convenience of control for almost every smart devices

Complete Smart Home Solution

- Supports Zwave, WAGO, Modbus, LAN communication
- Convenience & Lifestyle
- IAQ Management
- Energy Management
- Home Security Solution
- Google Home Enabled

Note: Residential automatic control and system report is offered as optional software.




1. Google Home and the Google Home logo are trademarks of Google LLC.
2. Amazon, Alexa and all related logos are trademarks of Amazon.com, Inc. or its affiliates.
3. Z-Wave® is a registered trademark of Sigma Designs and its subsidiaries in the United States and other countries.

VRV Smart Centralised Control Solution (Smartphone Controller for Home (Lite Version) :DCPH02)

Designed to enhance the comfort and convenience for homeowners, offering complete control of core functions in Daikin Airconditioning system remotely through app access

Note: Residential automatic control and system report is offered as optional software.



Control Systems


Hotel Air Conditioning Solution (Smartphone Controller for Hotel :DCPL01)

The smart hotel air conditioning solution for effective air conditioning operation that maximize guest comfort and minimize energy consumption in a hotel

Air Conditioning Guestroom Interlocking Management

- Automatic air conditioning control based on check in/out signal, key card signal and window open/close signal
- Guest comfort


Note: The Smartphone Controller for Hotel controller has to be used with Smartphone Controller for Office / Smartphone Controller for Office (Touchscreen Controller) / Smartphone Controller for Office (Controller Extension) controller as building controller.



Villa Air Conditioning Solution (Smartphone Controller for Resort :DCPR01)

Designed to enhance the comfort and convenience for each villa according to use by guests

- Automatic air conditioning control based on check in/out signal, key card signal and window open/close signal
- Guest comfort



Streamer Duct Chamber

New BDEZ-A Series

Utilising Streamer technology to ducted indoor unit



Display panel


Lineup

Model	BDEZ500A60VE	BDEZ500A140VE	BDEZ500A510VE
Airflow range (CMH)	80-600	500-1400	1200-5100



Presentation Movie

Filters Mechanism



Streamer Duct Chamber Internal Structure

Dust collection filter (MERV 14) catches bacteria and viruses and prevents them from entering the room.

Dust Collection Filter (MERV 14)

Particulate matter as small as 2.5 µm (micrometers) can be breathed deep into the lungs. Rest assured that your air remains clean as the filter is able to remove particulate matter as small as PM2.5 with Dust Collection Filter (MERV 14) ratings in accordance to ASHRAE 52.2 Standards.

Product: Streamer Duct Chamber (Line-Up 1,2,3)
 Testing Organization: Goldensea
 Test Number: GS-GL-0817-2021-01/02, GS-GL-0818-2021-01
 Test Method: Filter performance test based on ASHRAE 52.2-2017
 Test result: The filter meets MERV 14 rating.


Standard 52.2 Minimum Efficiency Reporting Value	Composite Average Particle Size Efficiency, % in Size Range, µm		
	Range 1 (0.3-1.0)	Range 2 (1.0-3.0)	Range 3 (3.0-10.0)
14	75%	90%	95%

Dust Collection Filter (MERV 14) Replacement Period

Air Quality Condition	Dust concentration (µg/m ³)		Replacement period
	PM2.5	PM10	
Case 1	18.5	28.5	12 months
Case 2	35	65	6 months

Replace with a new filter when clogging occurs. The left table shows the approximate replacement time when daily operation is 9 hours and annual operation are 240 days. It shows the calculation result for two air conditions. Adjust the replacement timing in consideration of the air environment in the area where the product is actually installed and the time and day it is operated.

Deodorising Filter




Streamer Technology



Streamer technology decomposes harmful substances caught by the filter. See page 3-4

Streamer technology is a unique Daikin technology that decomposes viruses, bacteria, allergens such as pollen, hazardous chemical substances such as formaldehyde, and odours with strong decomposing power.




Streamer Duct Chamber




Connectable Air Conditioning

Multiple combination of ducted unit




* Any ducted type indoor units except FXDSQ/FXDQ models are connectable. Refer to option list of indoor unit for details of connected models.



Installation Conditions


Duct Type Indoor Unit

Streamer Duct Chamber must be installed before the air conditioner unit to avoid condensation issue due to cold air draft.




Outdoor-Air Processing Unit

Streamer Duct Chamber must be installed before the air conditioner unit to avoid condensation issue due to cold air draft. Besides, it can avoid the outdoor-air processing unit from getting dirty with the outdoor polluted air.






Heat Reclaim Ventilator

Streamer Duct Chamber can be installed in either Location 1 or Location 2. However, Location 1 is highly recommended in order to avoid VAM from getting dirty with the outdoor polluted air.



Specifications


MODEL	  		
	BDEZ500A60VE	BDEZ500A140VE	BDEZ500A510VE
Power supply	1 phase, 220-240 V/220 V, 50/60 Hz		
Casing dimensions	H (mm)	269	318
	W (mm)	419	1419
	D (mm)	418	653
Operating temperature	-10 to 50		
Operating humidity	Max. 80%RH		
Airflow rate	CMH	80 - 600	500 - 1400
Initial pressure drop	Pa	5 - 59	18 - 76
Dust collection filter (MERV 14) lifespan	Months (based on median CMH)	12	12
Weight	kg	13	38
Power consumption	W	6.0	11.0
Sound pressure level	No increase in Sound Pressure Level as overall system		
Filters quantity	Pre-filter	1	2
	Dust collection filter (MERV14)	1	2
	Deodorising filter	1	2
Replacement filter dust collection filter (MERV 14)		BAFH500A60 (1pc)	BAFH500A140 (2pcs)
Dimensions HxWxD	mm	221 x 392 x 50 (referring to 1pc only)	
Working method	DP sensor		

Precision Piping Method

A smarter way to connect refrigerant piping for VRF installations

Using TIGHTFIT (Daikin Gas Tight Joint) ensures safety, easy connection work and quick installation. In addition, heavy equipment, such as gas cylinders used for brazing, becomes unnecessary.


TIGHTFIT




TIGHTFIT (Daikin Gas Tight Joint)

- ✓ Easy installation by tightening with a wrench
- ✓ Metal seal to eliminate gas leaks
- ✓ Function to prevent insufficient nut tightening

Non-Brazed REFNET Joint New




- ✓ Non-Brazed connection
- ✓ Directly connects to Tightfit
- ✓ Insulation material conforms to British Standard fire protection



Innovative problem solving for VRF refrigerant piping installation


Shorter installation time

Easy piping work significantly shortens installation time. This makes installation possible for projects with short deadlines while reducing labor costs.



Safety for Fire


Because no brazing is involved, installation is safe with no danger of fire. This makes it ideal for installation in renewal projects.



Easy work

- Torque for tightening nut is lower than the torque of the flare nut.
- Work can be safely performed even in high locations.
- Two wrenches are used to tighten pipe connection. (No special tools required.)


Installation completed in 4 steps



Torque for tightening flare nut: 75Nm

Torque for Tightfit tightening: 19Nm


LOW TORQUE (75% reduction for $\phi 15.9$ copper pipe)



Easy piping connection for residential installations

When installing a small-size VRF in a residential home, we suggest using a header pack to reduce construction and simplify installation. This also eliminates the need for heavy tools.


HEADER PACK




HEADER PACK (Packaged Refnet Headers)

- ✓ Time Saver using Quick Flare Nut Connection
- ✓ Compact design with low height
- ✓ Connects up to 4 and 6 indoor units

Soft copper pipe






Outdoor unit


Indoor unit

TIGHTFIT



There are also cases where Tightfit is used.


HEADER PACK




Connect by Daikin Gas Tight Joint or flare

Easy installation


Flare nut connection



Refnet joint x5



HEADER PACK x1



Flare connection


Soft copper pipe

HEADER PACK

Benefits of Header Pack

- Ideal for small-size properties and condominiums
- Fewer piping connections
- Flare connection makes it easy to connect
- Easy installation with substantial use of soft copper pipes (Good workability in high places and narrow spaces.)

Easy connection



Beam

Duct

Soft copper pipe

Precision Piping Method


TIGHTFIT (Daikin Gas Tight Joint)

Easy to fit, tight connection

Quality assurance

Conforms to ISO14903

Tightness test: P=4.3MPa;
Test medium: 100% Helium, T=22°C
Max leakage: 7.5×10^{-7} Pa·m³/s or less.
Vacuum test: 6.5kPa in absolute




TIGHTFIT full lineup

Standard Joint		Asymmetry Joint		90° Bend Joint		Test Plug	
Size	Model name	Size	Model name	Size	Model name	Size	Model name
ø6.35	SDGTB06	ø9.52-6.35	SDGTB0906	-	-	ø6.35	SDGTKB06
ø9.52	SDGTB09	ø12.70-9.52	SDGTB1209	-	-	ø9.52	SDGTKB09
ø12.70	SDGTB12	ø15.88-12.70	SDGTB1512	-	-	ø12.70	SDGTKB12
ø15.88	SDGTB15	ø19.05-15.88	SDGTB1915	-	-	ø15.88	SDGTKB15
ø19.05	SDGTB19	ø22.22-19.05	SDGTB2219	-	-	ø19.05	SDGTKB19
ø22.22	SDGTB22	ø25.40-22.22	SDGTB2522	ø22.22	SDGTLB22	ø22.22	SDGTKB22
ø28.58	SDGTB28	ø28.58-25.40	SDGTB2825	ø28.58	SDGTLB28	ø28.58	SDGTKB28
ø34.92	BDGTA34	ø34.92-28.58	SDGTB3428	-	-	-	-
ø41.28	BDGTA41	-	-	-	-	-	-


Dimension & weight

Standard Joint




Size	L (mm)	W (mm)	Weight (g)
ø6.35	50.4	15.0	43.0
ø9.52	55.0	19.9	79.0
ø12.70	59.0	23.5	113.0
ø15.88	74.0	30.0	210.0
ø19.05	76.8	34.6	273.0
ø22.22	83.4	40.2	292.0
ø28.58	88.0	46.7	515.0
ø34.92	101.5	51.1	686.0
ø41.28	103.5	58.3	881.0

Asymmetry Joint




Size	L (mm)	W (mm)	Weight (g)
ø9.52-6.35	52.7	19.9	67.0
ø12.70-9.52	57.5	23.5	101.0
ø15.88-12.70	65.0	30.0	164.0
ø19.05-15.88	76.8	34.6	244.0
ø22.22-19.05	81.5	40.2	358.0
ø25.40-22.22	85.8	43.5	444.0
ø28.58-25.40	88.1	46.7	505.0
ø34.92-28.58	101.5	51.1	645.0

90° Bend Joint



Size	L (mm)	Weight (g)
ø22.22	120.0	655.7
ø28.58	145.0	968.4

Test Plug




Size	L (mm)	W (mm)	Weight (g)
ø6.35	43.0	15.0	53.0
ø9.52	44.0	20.0	67.6
ø12.70	46.0	23.0	73.4
ø15.88	50.0	30.0	96.6
ø19.05	52.0	34.0	111.7
ø22.22	54.0	40.0	135.6
ø28.58	54.0	46.0	146.0

New Non-Brazed REFNET Joint

Direct connection to TIGHTFIT

This kit is designed as a refrigerant branch kit for connecting the main and branch pipes of VRV indoor units without brazing.

Lineup



※ Insulation included

Indoor unit total capacity index	Model name	
	2 pipes	3 pipes
X < 290	BHRG26A33T	BHRG25A33T
290 ≤ X < 640	BHRG26A72T	BHRG25A72T
640 ≤ X	BHRG26A73T	BHRG25A73T

Case 1: If the pipe of the REFNET joint has the same size as the field pipe, cut it at the same size and connect it to the field pipe with the standard type of Daikin Gas Tight Joint.


Case 2: If the pipe of the REFNET joint has not the same size as the field pipe, use the Asymmetry joint (Reducer).

HEADER PACK (Packaged Refnet Headers)

Simple & Quick Installation

HEADER PACK Lineup



Model name	Outdoor unit side	Indoor unit side (Flare)		Indoor unit total capacity index	Dimension (mm)			
	Liquid / Gas (mm)	Port	Liquid / Gas (mm)		H	D	W	
BHF6RHP6Z	9.5 / 15.9 (Flare)	4	Large x1 Small x3	φ9.5 / φ 15.9 φ 6.4 / φ 12.7	≤ 150	135	143	559
BHF6ARHP6Z	9.5 / 15.9 (Flare)	6	Large x2 Small x4	φ9.5 / φ 15.9 φ 6.4 / φ 12.7	≤ 150	135	143	623
BHF8RHP6Z	9.5 / 19.1 (Daikin Gas Tight Joint)	6	Large x3 Small x3	φ9.5 / φ 15.9 φ 6.4 / φ 12.7	≤ 200	135	143	623
BHF10RHP6Z	9.5 / 22.2 (Daikin Gas Tight Joint)	6	Large x3 Small x3	φ9.5 / φ 15.9 φ 6.4 / φ 12.7	< 290	135	143	623
BHF16RHP6Z	12.7 / 28.6 (Daikin Gas Tight Joint)	6	Large x3 Small x3	φ9.5 / φ 15.9 φ 6.4 / φ 12.7	< 420	135	143	623



Active Filter Unit

BACF22E5 (Option) For VRV X (MAX) / A (MAX) series

In an electric power system, a harmonic is a voltage or current that is distorted and deviate from sinusoidal waveforms. The distorted waveforms occur from the composition of a frequency that is an integer multiple of the fundamental frequency of the power supply. Harmonics generated by power semiconductor devices can travel through wires and may have negative effects such as equipment malfunctions and damage, vibrations, strange noises, etc.




Specifications

MODEL	BACF22E5	
Power supply	3 φ, 380 – 415 V/380 V, 50/60 Hz	
Rated compensation capacity	4.6 kVA	
Installation environment	Outdoors	
System	Cooling	Forced air cooling (built-in fan)
	Inverter	Voltage type
Operation	Load current: Starting 5.5 A or more, stopping 4.0 A or less	
Error display	Displayed on the display board when an error occurs	
Operation characteristics	Harmonic compensation target order: 2 nd to 23 rd However, the residual rate changes depending on the power supply impedance.	
Dimensions (HxWxD)	723 x 334 x 249 mm	
Weight	22 kg	


Advantages of Active Filter

Daikin's Active Filter unit can drastically reduce harmonics, preventing damages from harmonics and extending equipment lifespan.



*Total Harmonic Current (THC) is the accumulated currents of the orders 2 to 23 that contribute to the distortion of the current waveform. This value is particularly useful in determining the required characteristics for installation of modern active harmonic filters.

Field Wiring



* Refer to the Engineering Data Book for details.

